

Aluminum Electrolytic Capacitor Specification				
Series	KLH	63 V 330 $\mu$ F	Part No.	KLH-063V331MG200-T/A5.0
Customer No.	/		Case size	$\Phi$ D 10 X L 20
Specification	Items		Standard	
	Operating temperature range		- 40 ~ + 105 $^{\circ}$ C	
	Capacitance tolerance		$\pm$ 20% ( 20 $^{\circ}$ C , 120Hz )	
	Dissipation factor (MAX)		( Less than ) 0.09 ( 20 $^{\circ}$ C , 120Hz )	
	Leakage current (MAX)		( Less than ) 207.9 $\mu$ A ( 20 $^{\circ}$ C 63 V 2 min )	
	Impedance (MAX)		0.15 $\Omega$ (100kHz, 20 $^{\circ}$ C)	
	Ripple current (MAX)		1100mArms ( 100kHz , 105 $^{\circ}$ C )	
	Load life		5000hrs	
Outline	Sleeving pipe basic		PVC	
	( Dimensions )			
	<p style="text-align: center;">(unit):mm</p>			
Recorder	(The first edition) : 2017-7-1			
Wrote by: LUOLI		Checked by: DINGCHANGHUA		Approved by: SHENZHIHONG