Shinland

Each Ray is brighter in Shinland

SL-E-132EA

Details

		LED Source
Material:	URC2500	
Cover Material:	PC	
Process:	Vaccum Aluminum Plating PC	XPH35
Length:	131.4mm	XP-L
Width:	24.2mm	XP-G2/3
Height:	12.3mm	XP-E2
Matched Cover:	SL-E-132EA-COVER-00	
ROSH Compliant:	YES	Square
Status:	Ready	Oslon

Optical Properties

Code	Typ. Angle	Typ. efficiency
SL-E-132EA-S	12°	90%
SL-E-132EA-F	34°	90%
SL-E-132EA-W	48°	90%

Photo





Matched

LUXEON T LUXEON TX LUXEON REBEL ES

Dimensional Figure SL-E-132EA

Measure Unit: mm





Shinland

Dimensional Figure SL-E-132EA-COVER-00

Measure Unit: mm







Distribution Curve Flux SL-E-132EA&SL-E-132EA-COVER-00





cd/klm C0 - C180 _____ C90 - C270





SL-E-132EA-S K:9.19cd/lm,LED:CERR132



SL-E-132EA-F K:2.97cd/lm,LED:CERR132



SL-E-132EA-W K:2.14cd/Im,LED:CERR132



Package Description

SL-E-132EA

Part NO.	Number per	Box Weigh	Box Size
Part NO.	Box(pcs)	(kg)	(cm)
SL-E-132EA-S	660	10. 48kg	60*32*40
SL-E-132EA-F	660	10. 68kg	60*32*40
SL-E-132EA-W	660	10.7kg	60*32*40
SL-E-132EA-COVER-00	600	8.08kg	60*32*40

Notes

- It is not allowed to scrub the reflective surface. If there is dust on the surface, please clean by soft cotton with little water.
- It is forbidden to clean with industrial solvent such as ethanol.
- Storage temperature: 0°C-40°C, and humidity:30%-95%
- Keep reflectors in package to void the dust.
- Prohibit the reflector touch with acid or alkaline solvent

About Shinland

Shenzhen Shinland Co. Ltd,one of the longest and most professional company in lighting optical field,have 20 years experience.Different from other factory which only have simple process, all aspects included R&D,making mold,injection molding ,vacuum coating and market support are our company own vertically integrated production .

Insisting on 'Quality First, Service First' and pragmatic, enterprising spirit,building the market by quality, casting our brand by credibility and integrity ,Shinland now become the leading supplier of lighting optical solution in China.

