


SCHEMATIC



SPECIFICATION

1. Rating : DC 30V 0.5A;
2. Contact resistance:  $\leq 0.03\Omega$ ;
3. Insulation resistance:  $\geq 100M\Omega$  (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-20N;
6. life test: 5,000 cycles.

8	HOUSING	1	PBT	
7	COVER	1	PBT	
6	6#CONTACT	1	PHOSPHOR BRONZE	Ag-Plating
5	5#CONTACT	1	H62 BRASS	Ag-Plating
4	4#CONTACT	1	H62 BRASS	Ag-Plating
3	3#CONTACT	1	PHOSPHOR BRONZE	Ag-Plating
2	2#CONTACT	1	PHOSPHOR BRONZE	Ag-Plating
1	1#CONTACT	1	PHOSPHOR BRONZE	Ag-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING
UNIT: MM		TYPE:		MODEL NO:
		PHONE JACK		L-KLS1-TSJ3.5-023
DESIGNER		PAPER NO:		PAGE 1 OF 1
BY CHECK		TOLERANCE		SCALE
BY APPROVED		A4		VER
		±0.15		3:1
		±1.5'		1
<b>KLS ELECTRONIC CO., LTD</b>				