


SCHEMATIC



SPECIFICATION

- 1. Rating : DC 30V 0.5A;
- 2. Contact resistance:  $\leq 0.03\Omega$ ;
- 3. Insulation resistance:  $\geq 100M\Omega$  (DC250V);
- 4. Withstand voltage: 500VAC ;
- 5. Insertion and extraction force: 3-20N;
- 6. Life test: 5,000 cycles.

8	HOUSING	1	PA66/PBT	
7	COVER	1	PC	
6	AXIS SUPPORT	1	H59 BRASS	Ni-Plating
5	5#CONTACT	1	PHOSPHOR BRONZE	Cu-Sn-Plating
4	4#CONTACT	1	H62 BRASS	Cu-Sn-Plating
3	3#CONTACT	1	H62 BRASS	Cu-Sn-Plating
2	2#CONTACT	1	PHOSPHOR BRONZE	Cu-Sn-Plating
1	1#CONTACT	1	H62 BRASS	Cu-Sn-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

UNIT:MM	TYPE:	MODEL NO:	PAPER NO:	PAGE 1 OF 1	
	PHONE JACK	L-KLS1-TSJ3.5-024	TOLERANCE	ANGLES	SCALE
			$\pm 0.15$	$\pm 1.5^\circ$	3:1
DESIGNER			VER	1	
CHECK			<b>KLS ELECTRONIC CO., LTD</b>		
APPROVED					