

Aluminum Electrolytic Capacitor Specification

Series	PKRM	400 V 15 μ F	Part No.	PKRM-400V150MG160-T/A5.0
Customer No.	/		Case size	Φ D10 X L 16
Specification	Items		Standard	
	Operating temperature range		- 40 ~ + 105 $^{\circ}$ C	
	Capacitance tolerance		\pm 20% (20 $^{\circ}$ C , 120Hz)	
	Dissipation factor (MAX)		(Less than) 0.15 (20 $^{\circ}$ C , 120Hz)	
	Leakage current (MAX)		(Less than) 180 μ A (20 $^{\circ}$ C 400 V 1 min)	
	Impedance (MAX)		/	
	Ripple current (MAX)		130 mArms (120Hz , 105 $^{\circ}$ C)	
	Load life		2000 hrs	
Outline	Sleeving pipe basic		PET	
	(Dimensions)			
	<p style="text-align: center;">Copper clad steel wire(tinned)</p> <p>The drawing shows a side view of the capacitor with a sleeve. Labels include: Vent, Sleeve, Markings, $\Phi 0.6 \pm 0.05$, $10 + 0.5$ MAX (height), 16 ± 1.5 max (length), 15min (lead length), and 4min (lead length). The end view shows a circular capacitor with two leads, labeled with Flat Rubber and Lead Space 5.0 ± 0.5. A note indicates [Remarks: Taping space: 5.0 ± 0.5] and the unit is mm.</p>			
Recorder	(The first edition) :2019-4-10			
Wrote by: LuoLi		Checked by: Caoguihua		Approved by: Shenzhihong