



Representative Image

Ref. No. 102080 | Cat. No. MCRA013AT5

Description: Screw terminal, 1NO+3NC, 120V/50-60Hz AC Bifreq. Coil (GE)

EAN 8425095020801

Products > Power devices > Contactors > 6. Series M: Auxiliary contactors 16A lth screw terminal

- Control circuit:
- Alternating current up to 600V
- Terminal numbering in accordance with EN 50011
- Fixing system for rapid and simple mounting by claming onto standard 35mm DIN rail (EN 50022)
- screw and push-on terminals protected against accidental contact in accordance with VDE 0106 T.100, VB94
- Printed circuit version
- Facility to mount instant or timed auxiliary contact blocks and voltage suppressor blocks
- Degree of protection IP20 in accordance with EN60529
- Conform to IEC/EN60947-1, EN/60947-5-1

Descriptors

Category | 6. Series M: Auxiliary contactors 16A lth screw terminal

Specifications

Series	Auxiliary minicontactors (lth = 16A)
Control circuit	AC
Terminal	Screw terminal
Control Voltage: AC Bifreq. Coil (at 50-60 Hz)	120 V
Contacts acc. To EN 50011	1NO+3NC
Number of contacts	4
Utilisation category AC15	110/120V - 6A, 220/240V - 6A, 380/400V - 4A, 415/440V - 4A, 500V - 2.5A, 660/690V - 1.5A
Utilisation category DC13	110V - 1.2A, 220V - 0.6A, 24V - 5A, 440V - 0.25A, 48V - 3.5A
Package (pcs)	20

Classifications

ETIM 5.0	EC000066
ETIM 6.0	EC000066

Dimensions

Weight	0.170 kg
--------	----------