

| | А | lluminum Ele | ectrolytic Capac | citor Specifica | ation |
|----------------------|---------------------------------|----------------|---------------------------------|-------------------|---|
| Series | RS | 50V10uF | Part No. | RS-0 | 50V010AX110-T5 |
| Customer no | | 1 | Case Size | | ФD 5 x L11 |
| Specification | Items | | Standard | | |
| | Operating temperature range | | -40~+105 ℃ | | |
| | Capcitance tolenrance | | ±20% (20±2℃,100Hz) | | |
| | Dissipation Factor (MAX) | | (Less than) 0.1 (20±2°C,100Hz) | | |
| | Leakage current (MAX) | | (Less than) 5 (20±2℃,50V 2 min) | | |
| | Impedance (MAX) | | 2.2 | | |
| | Ripple current (MAX) | | 100 mArms (100KHz,105℃) | | |
| | Lond life | | 4000hrs | | |
| Outline | Sleeve color | | Purple | | |
| | Marking color | | White | | |
| | (Dimensions) | | | | |
| | 5+0.5 MAX | Sleeve | 7 Ø0.5 | 4min [Remai | Unit(mm) 2±0.5 Lead space rks:Taping space:(5.0±0.5)] |
| Recorder | (The first edition): 2018-01-19 | | | | |
| Wrote by:Dengweiping | | Checked by: Zh | nangguang | Approved by:Liyan | |