


Surface Mount Aluminum Electrolytic Capacitor Specification

Series	MRW	16 V 330 μ F	Part No.	MRW-016V331MF070-T/R													
Customer No.	/		Case size	Φ D8X L7													
Specification	Items		Standard														
	Operating temperature range		- 40 ~ + 105 $^{\circ}$ C														
	Capacitance tolerance		\pm 20% (20 $^{\circ}$ C , 120Hz)														
	Dissipation factor (MAX)		(Less than) 26%(20 $^{\circ}$ C , 120Hz)														
	Leakage current (MAX)		(Less than) 52.8 μ A (20 $^{\circ}$ C 16 V 2 min)														
	ESR (MAX)		/														
	Ripple current (MAX)		230 mArms (120Hz , 105 $^{\circ}$ C)														
	Load life		2000 hrs														
Outline	Marking color		Blue														
	(Dimensions)																
	 <p style="text-align: right;">(unit):mm</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>ΦD</th> <th>L</th> <th>A</th> <th>B</th> <th>C</th> <th>W</th> <th>P\pm0.2</th> </tr> </thead> <tbody> <tr> <td>8</td> <td>7.0</td> <td>8.3</td> <td>8.3</td> <td>9.0</td> <td>0.7~1.1</td> <td>3.1</td> </tr> </tbody> </table>				Φ D	L	A	B	C	W	P \pm 0.2	8	7.0	8.3	8.3	9.0	0.7~1.1
Φ D	L	A	B	C	W	P \pm 0.2											
8	7.0	8.3	8.3	9.0	0.7~1.1	3.1											
Recorder	(The first edition) :2019-4-9																
Wrote by: Mengxiaocong		Checked by: Jianguyanyuan		Approved by: Huangxuehui													