



健隆投資有限公司
STRONG BASE INVESTMENT LTD.

Unit 17, 11/F., Hewlett Centre, 52-54 Hoi Yuen Road, Kwun Tong, Kowloon, Hong Kong.
Tel: (852) 2793 3293 Fax: (852) 2793 3096



Approval Sheet
(確認書)

編號 Ref. No.	180505-01
日期 Issued Date	2018-05-05

公司名稱 : **OZ**
 Company Name

產品編號 : **M1-05057ASR1**
 Part No.

產品種類 : **数码显示板**
 Category

產品描述 : **05 (5*7)陣列、共阳、超高亮紅色、黑面散射**
 Description

客戶產品編號 :
 Customer No.

備注 :
 Remarks

STRONG BASE			
ISSUER	APPROVER	CHECKER	ENGINEER
	曾雪昭	王金龙	郭清莲

Authorized Signature 客戶簽字				
部門 Department				
簽字 Signature				

工廠名稱: 宇之亮電子(深圳)有限公司
 工廠地址: 廣東省深圳市龍崗區橫崗鎮荷坳村金源工業區
 Company Name: Pretty Light (Shen Zhen) Limited
 Factory Address: jin-Yuan, Industrial Zone He-Ao Cun, Heng-Gang
 Zhen Long-Gang Area, Shen-Zhen City,
 TEL: (755) 8976 7353 FAX: (755) 89767754



健隆投資有限公司

STRONG BASE INVESTMENT LTD.

Unit 17, 11/F., Hewlett Centre, 52-54 Hoi Yuen Road, Kwun Tong, Kowloon, Hong Kong.

Tel: (852) 2793 3293 Fax: (852) 2793 3096



PART No: M1-05057ASR1

Client: OZ

Single Chip Light Electricity Characteristic Data

※Absolute Maximum Ratings at Ta=25°C

Parameter	Rating	Unit
Power Dissipation Per Chip	50	mW
Perk Forward Current Per Chip (Frequency 10KHz,1/10Duty Cycle)	60	mA
Reverse Voltage Per Chip	5	V
Operating Temperature Range	-20~+80	°C
Storage Temperature Range	-20~+85	°C
Storage Humidity	45%~85%	

※Electrical and Optical Characteristics at Ta=25°C

Parameter	Symbol	Condition	Color	Min	Typ	Max	Unit
Forward Voltage Per Chip	VF	IF=20mA	Red	1.7	2.0	2.5	v
Reverse Current	IR	VR=5V	-	-	-	50	uA
Luminous Intensity Per Chip	IV	IF=20mA	Red	30	45	60	mcd
Dominant Wave Length	λd	IF=20mA	Red	625	630	640	nm
Normal Forward Current	IF		All Color	5	10	20	mA

Note: Soldering Bath: not more than 4 seconds @260°C。The bottom ends of plastic reflector should be at least 2mm above the solder surface。


Soldering Iron: not more than 3 seconds @300°C under 30W。



PART No.: M1-05057ASR1

Client: OZ

PACKAGE DIMENSION (Unit: mm Tolerance: ±0.25)



INTERNAL CIRCUIT DIAGRAM

