



Representative Image

Ref. No. 112050 | Cat. No. CL02D301TB

Description: CL02D301TB Contactor 3-pole 12V DC

EAN 8017018120509

Home > Power devices > Contactors > 4. Series CL: Contactor for general purpose application 9-105A AC3

Series CL & RL, Three-pole contactor, Terminal: screw, Control Voltage (V): 12 V DC Max.oper.current AC1 (A): 32 Max.oper.current AC3 (A): 18 Admissible power 220V/230V (kW): 4 Admissible power 380V/400V (kW): 7,5 Aux.contacts: 1NC

Descriptors

Category	4. Series CL: Contactor for general purpose application 9-105A AC3
----------	--

Specifications

Series	Three-pole contactors from 9 to 105 A (AC3)
Control circuit	DC
Control Voltage: DC	12 V
Terminal type	Screw terminal
Max. operating current AC1 Non-inductive loads	32 A
Max. operating current AC3 Motors = 480V, 3-phase 50/60Hz	18 A
Electrical endurance: # operations AC3	1.7 x 10 ⁶
Aux Contacts	1NC
Type	For contactors type CL - D
Admissible power AC3 220V, 230V	4 kW
Admissible power AC3 380V, 400V	7.5 kW
Admissible power AC3 415V, 440V	7.5 kW
Admissible power AC3 500V	10 kW
Package (pcs)	5
Class	1. Contactors

Classifications

ETIM 5.0	EC000066
ETIM 6.0	EC000066

Dimensions

Weight	0.490 kg
--------	----------

Publications

Title	Publication No.	Publication Type
Auxiliary contactor RL4RD (pdf)		
Auxiliary contactor RL4RD (3DPDF format)	3D-00016-PDF	Drawings - CAD - 3D
Auxiliary contactor RL4RD (stp)		
Auxiliary contactor RL4RD (STEP format)	3D-00016	Drawings - CAD - 3D

Additional Documentation: Visit our [Publication Library](#) to find technical documentation, specifications, catalogues, promotional literature, 3D's,...