



Representative Image

## Ref. No. 110621 | Cat. No. CL03A400M6

Description: CL03A400M6 Contactor 4-pole 230V 50Hz / 60Hz AC

EAN 8425095106215

### Home > Power devices > Contactors > 4. Series CL: Contactor for general purpose application 9-105A AC3

Series CL & RL, 4-pole contactor, Terminal: screw, Control Voltage (V): 230 VAC Max.oper.current AC1 (A): 45 Max.oper.current AC3 (A): 25 Admissible power 220V/230V (kW): 17 Admissible power 380V/400V (kW): 29 Aux.contacts: -

## Descriptors

Category	4. Series CL: Contactor for general purpose application 9-105A AC3
----------	--

## Specifications

Series	Four-pole contactors from 25 to 140 A (AC1)
Control circuit	AC
Frequency Control Voltage: AC	50-60 Hz
Terminal type	Double clamp terminal
Max. operating current AC1 Non-inductive loads	45 A
Max. operating current AC3 Motors = 480V, 3-phase 50/60Hz	25 A
Electrical endurance: # operations AC1	2 x 10 <sup>6</sup>
Power contacts	4NO
Control Voltage: AC (50/60 Hz)	220-230 V
Admissible power AC1 220V, 230V	17 kW
Admissible power AC1 380V, 400V	29 kW
Admissible power AC1 415V, 440V	32 kW
Admissible power AC1 500V	39 kW
Package (pcs)	10
Class	1. Contactors

## Classifications

ETIM 5.0	EC000066
ETIM 6.0	EC000066

## Dimensions

Weight	0.490 kg
--------	----------

## Publications

Title	Publication No.	Publication Type
<a href="#">4-pole CL03A-CL04A (stp)</a>		
4-pole CL03A-CL04A (STEP format)	3D-00017	Drawings - CAD - 3D
<a href="#">CONACL03F</a>		
CONACL03 Front view	CONACL03F	Commercial Drawings
<a href="#">CONACL03R</a>		
CONACL03 Rear view	CONACL03R	Commercial Drawings
<a href="#">CONACL03L</a>		
CONACL03 Side view	CONACL03L	Commercial Drawings
<a href="#">CONACL03T</a>		
CONACL03 Total view	CONACL03T	Commercial Drawings
<a href="#">4-pole CL03A-CL04A (pdf)</a>		
4-pole CL03A-CL04A (3DPDF format)	3D-00017-PDF	Drawings - CAD - 3D

**Additional Documentation:** Visit our [Publication Library](#) to find technical documentation, specifications, catalogues, promotional literature, 3D's,...