

Kingtronics®

SB1240

FEATURE

FOR SURFACE MOUNTED APPLICATIONS

LOW PROFILE PACKAGE

BUILT-IN STRAIN RELIEF

EASY PICK AND PLACE

PLASTIC MATERIAL USED CARRIES UNDERWRITERS

LABORATORY CLASSIFICATION 94 V-0

EXTREMELY LOW VF

MAJORITY CARRIER CONDUCTION

HIGH TEMPERATURE SOLDERING : 260°C//10 SECONDS

AT TERMINALS

MECHANICAL DATA

CASE: DO-27

TERMINALS: SOLDER PLATED


POLARITY: INDICATED BY CATHODE BAND

WEIGHT: 0.04 ounce, 1.10 grams

SURFACE MOUNT SCHOTTKY BARRIER RECTIFIER

Reverse Voltage - 40 Volts Forward Current - 12.0 Amperes

DO-27



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 C ambient temperature unless otherwise specified

Resistive or inductive load

	Symbol	SB1240	UNITS
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	40	V
Maximum RMS Voltage	V_{RMS}	28	V
Maximum DC Blocking Voltage	V_{DC}	40	V
Maximum Average Forward Current .375 (9.5mm) lead length at $T_L=75$ C	$I_{(AV)}$	12.0	Amps
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Superimposed on Rated Load (JEDEC Method)	I_{FSM}	300	Amps
Maximum Instantaneous Forward Voltage at 12.0A	V_F	0.55	Volts
Maximum DC Reverse Current $T_A=25$ C	I_R	1.0	Am
at Rated DC Blocking Voltage $T_A=100$ C		20	
Maximum Thermal Resistance (NOTE 2)	R_{JA}	75	°C/W
	R_{JL}	20	
Operating Junction Temperature Range	T_J	-50 to +125	°C
Storage and Operating Temperature Range	T_{STG}	-55 to +150	°C

NOTES:1. Pulse test with PW=300 sec, 1% duty cycle 2 2. Mounted on P.C.Board with 8mm² (0.13mm think) copper pad areas

Kingtronics®

SB1240

Fig.1 - FORWARD CURRENT DERATING CURVE




Fig.2 - MAXIMUMNON-REPETITIVEPEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL FORWARD CHARACTERISTICS





FIG.4-TYPICAL JUNCTION CAPACITANCE



Kingtronics® International Company

Kingtronics® International Company

Website: www.kingtronics.com Email: info@kingtronics.com Tel: (852) 8106 7033 Fax: (852) 8106 7099

Kingtronics® International Company

Website: www.kingtronics.com Email: info@kingtronics.com Tel: (852) 8106 7033 Fax: (852) 8106 7099
