

SPECIFICATION FOR APPROVAL

CUSTOMER:				DATE:					
PART NO: LF - 70B (B15)				DWG.NO: SY2118131S9					
CUSTOMER PART NO:				CUST.DWG.NO:					
(1) DIMENSION(UNIT:mm) 				A	22.0 ± 1.0 m/m				
				B	18.0 ± 1.0 m/m				
				C	7.0 ± 1.0 m/m				
				D	15.0 ± 1.0 m/m				
				E	m/m				
				F	m/m				
				G	m/m				
				H	m/m				
				I	m/m				
				J	m/m				
				(2)ELECTRICAL REQUIREMENTS				(3)CASE COLOR B:BLACK W:WHITE G:GRAY	
Z	MIN 35 OHM	TEST FREQ	25 MHz						
Z	MIN 70 OHM	TEST FREQ	100 MHz						
Z	MIN OHM	TEST FREQ	MHz						
Z	MIN OHM	TEST FREQ	MHz						
(4)TEST INSTRUMENTS HP 4991A									
MATERIAL (ui)	1500 ± 25%			APPROVED BY 吳載敏 CHECKED BY 張明德 DRAWN BY Vicky					
CORE	UH-12×15×7								
WIRE	φ 0.6 × 100 mm								
WINDING	1 Ts								

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw

TEST DATA

CUSTOMER :				DATE :					
PART NO: LF - 70B (B15)				DWG.NO: SY2118131S9					
CUSTOMER PART NO :				CUST.DWG.NO :					
IMPEDANCE				DIMENSION (UNIT : mm)					
FREQ	25 MHz	100 MHz		A	B	C	D		
SPEC	MIN 35 OHM	MIN 70 OHM		22.0 ± 1.0	18.0 ± 1.0	7.0 ± 1.0	15.0 ± 1.0		
1	55.6	117.3		22.41	18.35	7.23	14.88		
2	55.1	115.8		22.23	18.29	7.12	14.51		
3	54.3	116.2		22.31	18.28	7.13	14.78		
4	53.4	116.3		22.41	18.30	7.18	14.60		
5	53.2	115.7		22.25	18.33	7.20	14.80		
6	55.6	117.2		22.34	18.32	7.19	14.65		
7	51.9	115.4		22.40	18.28	7.23	14.56		
8	55.5	115.3		22.35	18.35	7.18	14.83		
9	55.7	116.2		22.26	18.31	7.14	14.65		
10	52.9	115.8		22.30	18.32	7.12	14.61		
X	54.3	116.1		22.33	18.31	7.17	14.69		
R	3.8	2.0		0.18	0.07	0.11	0.37		
REMARK: 產品不能有明顯缺陷、污損；產品缺口長、寬在 1.2mm 以下， 深在 0.7mm 以下。						APPROVED BY			
						吳載敏			
						CHECKED BY			
				張明德					
				DRAWN BY					
				Vicky					

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw

LF-70B (B15)

