



Position	Dimension			
	A	B	C	D
06	7.62	5.08	10.16	7.62
08	10.16	7.62	10.16	7.62
14	17.78	15.24	10.16	7.62
16	20.32	17.78	10.16	7.62
18	22.86	20.32	10.16	7.62
20	25.40	22.86	10.16	7.62
24	30.48	27.94	10.16	7.62
24	30.48	27.94	17.78	15.24
28	35.56	33.02	10.16	7.62
28	35.56	33.02	17.78	15.24
32	40.64	38.10	17.78	15.24
40	50.80	48.26	17.78	15.24
42	53.34	51.00	17.78	15.24

**ORDER INFORMATION**

Z B 1 0 1 1 - X X

X

X

X

SERIES NO

No. OF CONTACTS  
06 08 12 14 16 18  
20 24 28 32 40 42

CENTRAL SUPPORT

Y: W/  
N: W/D

WIDTH DIM D

A: 7.62MM(06~28P)  
B: 15.24MM(24~42P)

CONTACT PLATING

1: FULL GOLD  
3: FULL TIN

- NOTES:
- ELECTRICAL CHARACTERISTICS:
    - CONTACT RESISTANCE: 20mΩ Max.
    - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC(rms) FOR 1 MINUTE.
    - INSULATION RESISTANCE: 10000MΩ Min.
  - ENVIRONMENT CHARACTERISTICS:
    - TEMPERATURE: -20°C~+105°C.

**IC SOCKET PITCH 2.54mm TYPE**

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG	SK	DATE 2018-5-25	SIZE A4		UNITS MM
CHK		DATE	UNITS		SCALE
APP		DATE			

**ZB1011-XXP**

**ZHONGBA**  
NINGBO ZHONGBA PHOTOVOLTAIC TECHNOLOGY CO.,LTD

DWGNO