

## SHIELDED SMD POWER INDUCTORS / SCI TYPE

### FEATURES


- ◆ Low DC resistance
- ◆ Suitable for large currents
- ◆ Available in magnetically shielded
- ◆ Small size with the electrode attached to it





### APPLICATIONS

- ◆ Power supply for VTRs.
- ◆ Portable communication equipment.
- ◆ LCD televisions.
- ◆ DC to DC converters, etc.

### ORDERING CODE



### DIMENSIONS (UNIT: mm)



A	5.0 (MAX)	m/m
B	3.0 (MAX)	m/m
C	4.5 (REF)	m/m
D	1.6 (REF)	m/m

## SHIELDED SMD POWER INDUCTORS / SCI TYPE

### ELECTRICAL CHARACTERISTICS FOR SCI4D28

Part No.	Inductance ( $\mu$ H)	RDC ( $\Omega$ )	IDC (A)
SCI4D28-1R0 □	1.0	0.030	5.00
SCI4D28-1R2 □	1.2	0.030	4.00
SCI4D28-1R5 □	1.5	0.030	3.70
SCI4D28-1R8 □	1.8	0.031	3.50
SCI4D28-2R2 □	2.2	0.031	3.00
SCI4D28-2R7 □	2.7	0.035	2.90
SCI4D28-3R3 □	3.3	0.049	2.30
SCI4D28-3R9 □	3.9	0.058	2.20
SCI4D28-4R7 □	4.7	0.072	2.10
SCI4D28-5R0 □	5.0	0.088	2.00
SCI4D28-6R8 □	6.8	0.090	1.70
SCI4D28-8R2 □	8.2	0.120	1.50
SCI4D28-100 □	10	0.128	1.40
SCI4D28-120 □	12	0.132	1.23
SCI4D28-150 □	15	0.149	1.00
SCI4D28-180 □	18	0.250	1.00
SCI4D28-220 □	22	0.255	0.95
SCI4D28-330 □	33	0.258	0.65
SCI4D28-390 □	39	0.400	0.65
SCI4D28-470 □	47	0.478	0.63
SCI4D28-101 □	100	1.000	0.30
SCI4D28-151 □	150	1.500	0.25
SCI4D28-181 □	180	1.540	0.25
SCI4D28-221 □	220	2.000	0.20
SCI4D28-331 □	330	4.000	0.20

\* 100 $\mu$ H 以上 Test Frequency : 1KHZ/1V

\* 100 $\mu$ H 以下 Test Frequency : 100KHZ/0.1V

CORE MASTER ENTERPRISE CO., LTD.



<http://www.coremaster.com.tw>