



DG32-A - 03P - 1Y - 00A (H)
 (Series No.) (Poles)(Single Pitch) (Color) : 1.(Grey)
 2.(Blue)
 3.(Black)
 4.(Green)
 5.(Orange)
 6.(Red)
 7.(Transparent)
 8.(Yellow)
 9.(White)

7.RoHS Compliance

Pitch range	in		mm		Nominal dimension	range	
	Over	To	Over	To		Over	To
6	TO	10	TO	30	60	100	150
10	TO	24	TO	30	60	100	150
15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30
							±2°

- NOTES1:
- UL Standard
 - Rated voltage/current : 600V / 120A
 - Torque value : M6 , 22.15Lb.in
 - Wire range : 20~2AWG
- NOTES2:
- Dimension shall be interpreted per ASME Y14.5-2009
 - Pitch : 28.0mm, Poles : 03P
 - Stripping length : 18~19mm
 - Withstanding voltage : AC2000V/1Min
 - Operating temperature : -40°C~+125°C
 - Undimensioned tolerances:

REVISION RECORD			
REV	ECN	DESCRIPTION	DRFT DATE

PART NO. : /		NAME: DEGSON 宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO.,LTD	
APPD: /	CHKD: /	TITLE: CUSTOMER DRAWING	
DRAFT: /		DRAWING NO. : /	REV: DO
THIRD ANGLE PROJECTION		SCALE: 1:1	SHEET: 1/1

A 8 7 6 5 4 3 2 1