


SPECIFICATION FOR APPROVAL

CUSTOMER:				DATE:			
PART NO: CB1608-222Y-N				DWG.NO: TE2087477			
CUSTOMER PART NO:				CUST.DWG.NO:			
(1) DIMENSIONS (UNIT: mm) 				A	1.6 ± 0.2	m/m	
				B	0.8 ± 0.2	m/m	
				C	0.8 ± 0.2	m/m	
				D	0.3 ± 0.2	m/m	
				E		m/m	
				F		m/m	
				G		m/m	
				H		m/m	
				I		m/m	
				J		m/m	
(2) ELECTRICAL REQUIREMENTS							
Z (Ω)	2200 ± 25%	TEST FREQ	100MHz / 100mV				
RDC (Ω)	0.8 (MAX)	TEST FREQ					
IDC (mA)	50 (MAX)	TEST FREQ					
TEST INSTRUMENTS HP4338A MILLIOHMMETER HP4291B RF IMPEDANCE/MATERIAL ANALYZER				APPROVED BY 吳載敏			
				CHECKED BY 張明德			
				DRAWN BY 黃慧診			

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB: www.coremaster.com.tw

TEST DATA

CUSTOMER :				DATE :					
PART NO: CB1608-222Y-N				DWG.NO: TE2087477					
CUSTOMER PART NO :				CUST.DWG.NO :					
ITEM	Z (Ω)	RDC (Ω)	IDC (mA)	DIMENSION (UNIT : mm)					
				A	B	C	D		
FREQ	100MHz / 100mV								
SPEC	2200 ± 25%	0.8 (MAX)	50 (MAX)	1.6 ± 0.2	0.8 ± 0.2	0.8 ± 0.2	0.3 ± 0.2		
1	2234.1	0.658	OK	1.61	0.82	0.83	0.28		
2	2204.2	0.654	OK	1.62	0.80	0.81	0.30		
3	1884.3	0.683	OK	1.61	0.81	0.82	0.28		
4	1918.8	0.651	OK	1.64	0.83	0.81	0.29		
5	2259.2	0.645	OK	1.61	0.80	0.81	0.28		
6	2286.2	0.663	OK	1.63	0.81	0.83	0.30		
7	2205.1	0.623	OK	1.62	0.80	0.82	0.31		
8	2199.9	0.642	OK	1.61	0.82	0.81	0.28		
9	2164.8	0.662	OK	1.62	0.81	0.82	0.28		
10	2268.6	0.624	OK	1.62	0.80	0.81	0.29		
\bar{X}	2162.5	0.65		1.62	0.81	0.82	0.29		
R	401.9	0.06		0.03	0.03	0.02	0.03		
						APPROVED BY 吳載敏			
						CHECKED BY 張明德			
						DRAWN BY 黃慧診			

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB: www.coremaster.com.tw

CB1608-222Y-N

