





A	1		2			3		
	Female insert (mating shield)	Contact code	Rated Current	Rated Voltage	Withstand voltage	Insulation resistance	Contact resistance	Contact Diameter
		02	7	250	1500	1500	5	Ø1.5
B		03	7	250	1500	1500	5	Ø1.5
		04	7	250	1500	1500	5	Ø1.5
		05	6	250	1500	1500	5	Ø1.5
C		5A	5	50	500	1000	5	Ø1.5
		06	5	250	1500	1500	5	Ø1.5
D		07	5	50	800	1000	5	Ø1.5
		08	5	50	500	1000	5	Ø1.5
E		12	5	50	500	1000	3	Ø1.0
		14	5	50	500	1000	3	Ø1.0
F		16	5	50	500	1000	3	Ø1.0
		19	5	50	500	1000	3	Ø1.0
G		24	5	50	500	1000	3	Ø0.5
	UNIT	A	V	V.A.C	MΩ	mΩ	mΩ	mm



Front view



Back view

Order information

L-KLS15-253-J09-XX M3

- L: RoHS
- J09: C091 Miniature Circular Connector
- XX: Contacts Code
- M3: Soldering Connectors, Panel mount, Rear lock, Female Pin

GENERAL TOLERANCE

X: ±0.60
.X: ±0.38
.XX: ±0.25

ANGLE TOLERANCE

X: ±5°
.X: ±3°
.XX: ±2°

Draw by:	PROJECTION	UNITS	mm
Check by:	SHEET SIZE	A4	
SCALE			

Description: Soldering Connectors, Panel mount, Rear lock, Female, C091 Miniature Circular

KLS P/N: KLS15-253-J09-XXM3

KLS ELECTRONIC CO., LTD.

