


**Ref. No. 430636 | Cat. No. FDN36TD125GD**
**Description: FDN 160 Breaker Icu 50kA/415VAC Ue 690VAC 3P 3trips - 125A LTMD**
**EAN 5050096306369**
**Home > Industrial Circuit Breakers > Moulded Case Circuit Breakers**

Rated at 160A, the FD160 frame size is designed for use in both a DIN-rail environment with modular equipment and in industrial applications. It is supplied with IPXXB terminals suitable for direct connection of one or two conductors totalling up to 95 mm<sup>2</sup> and is available as a thermal-magnetic breaker(LT,ST). The FD160 bridges the gap between residential miniature circuit breakers and industrial moulded case circuit breakers.


**Descriptors**

Category	Moulded Case Circuit Breakers
----------	-------------------------------

**Specifications**

Series	Circuit breaker (complete breaker)
In (A)	125 A
Number of poles	3P
Trips	3 trips
Frame type	D frame (63A/160A)
Rating frame (A)	160 A
Short-circuit capacity (kA)	Normal 50 kA
Trip Unit	Line protection (thermal) delayed
Measurements	130x81x85 mm
Ui (V)	750 V
Ir (A)	100-125 A
IEC 230VAC	85 kA
IEC 400VAC	50 kA
IEC 440VAC	30 kA
IEC 500VAC	22 kA
IEC 690VAC	8 kA
IEC 690VAC Icu	8 kA
IEC 690VAC Ics	4 kA
IEC 250VDC	40 kA
IEC 440VDC	40 kA
IEC 500VDC	40 kA
NEMA 240V	65 kA
NEMA 480V	36 kA
Im (A)	1250 A

**Classifications**

ETIM 5.0	EC000228 - Power circuit-breaker for trafo/generator/installation protection
----------	--

## Classifications

ETIM 6.0	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 7.0	EC000228 - Power circuit-breaker for trafo/generator/installation protection

## Dimensions

Weight	1.050 kg
--------	----------

## Package Information

Standard packing	1
------------------	---