



Representative Image

**Ref. No. 109197 | Cat. No. CL00A301T1**
**Description: CL00A301T1 Contactor 3-pole 24V 50/60Hz**
**EAN 8017018091977**
**Home > Power devices > Contactors > Series CL - Contactor series for General Purpose application**

Series CL &amp; RL, Three-pole contactor, Terminal: screw, Control Voltage (V): 24 VAC Max.oper.current AC1 (A): 25 Max.oper.current AC3 (A): 9 Admissible power 220V/230V (kW): 2,2 Admissible power 380V/400V (kW): 4 Aux.contacts: 1NC

**Descriptors**

Category	Series CL - Contactor series for General Purpose application
----------	--

**Specifications**

Series	Three-pole contactors from 9 to 105 A (AC3)
Control circuit	AC
Frequency Control Voltage: AC	50-60 Hz
Terminal type	Screw terminal
Non-inductive loads AC1	25 A
Motors = 440V, 3-phase 50/60Hz AC3	9 A
Electrical endurance: # operations AC3	2 x 10 <sup>6</sup>
Aux Contacts	1NC
Control Voltage: AC	24 V
Admissible power AC3 220V, 230V	2.2 kW
Admissible power AC3 380V, 400V	4 kW
Admissible power AC3 415V, 440V	4 kW
Admissible power AC3 500V	5.5 kW
Package (pcs)	5

**Classifications**

ETIM 5.0	EC000066 - Power contactor, AC switching
ETIM 6.0	EC000066 - Power contactor, AC switching
ETIM 7.0	EC000066 - Power contactor, AC switching

**Dimensions**

Weight	0.295 kg
--------	----------