

**Ref. No. 109604 | Cat. No. CL07A300M1**
**Description: CL07A300M1 Contactor SLA Plus 3-pole 24V 50/60Hz**
**EAN 8425095096042**
**Home > Power devices > Contactors > Series CL - Contactor series for General Purpose application**

Series CL & RL, Three-pole contactor, Terminal: screw, Control Voltage (V): 24 VAC Max.oper.current AC1 (A): 110 Max.oper.current AC3 (A): 65 Admissible power 220V/230V (kW): 18,5 Admissible power 380V/400V (kW): 30 Aux.contacts: -



Representative Image

**Descriptors**

Category	Series CL - Contactor series for General Purpose application
----------	--

**Specifications**

Series	Three-pole contactors from 9 to 105 A (AC3)
Control circuit	AC
Frequency Control Voltage: AC	50-60 Hz
Terminal type	Double clamp terminal
Non-inductive loads AC1	110 A
Motors = 440V, 3-phase 50/60Hz AC3	65 A
Electrical endurance: # operations AC3	1.7 x 10 <sup>6</sup>
Type	For contactors type CL - D
Control Voltage: AC	24 V
Admissible power AC3 220V, 230V	18.5 kW
Admissible power AC3 380V, 400V	30 kW
Admissible power AC3 415V, 440V	37 kW
Admissible power AC3 500V	40 kW
Package (pcs)	10

**Classifications**

ETIM 5.0	EC000066 - Power contactor, AC switching
ETIM 6.0	EC000066 - Power contactor, AC switching
ETIM 7.0	EC000066 - Power contactor, AC switching

**Dimensions**

Weight	1.090 kg
--------	----------