


Ref. No. 112146 | Cat. No. CL08E300MD
Description: CL08E300MD Contactor 3-pole 24-48V AC/DC
EAN 8425095121461
Home > Power devices > Contactors > Series CL - Contactor series for General Purpose application

 Series CL & RL, Coil with electronic module, Control Voltage (V): 24-28 AC/DC Max.oper.current AC1 (A): 110
 Max.oper.current AC3 (A): 80 Admissible power 220V/230V (kW): 22 Admissible power 380V/400V (kW): 37
 Aux.contacts: -


Representative Image

Descriptors

Category	Series CL - Contactor series for General Purpose application
----------	--

Specifications

Series	Three-pole contactors from 9 to 105 A (AC3)
Control circuit	AC/DC
Terminal type	Double clamp terminal
Non-inductive loads AC1	110 A
Motors = 440V, 3-phase 50/60Hz AC3	80 A
Electrical endurance: # operations AC3	1.5 x 10 ⁶
Type	Coil with electronic module for contactors CL - E
Admissible power AC3 220V, 230V	22 kW
Admissible power AC3 380V, 400V	37 kW
Admissible power AC3 415V, 440V	45 kW
Admissible power AC3 500V	45 kW
Package (pcs)	1

Classifications

ETIM 5.0	EC000066 - Power contactor, AC switching
ETIM 6.0	EC000066 - Power contactor, AC switching
ETIM 7.0	EC000066 - Power contactor, AC switching

Dimensions

Weight	1.120 kg
--------	----------