


**Ref. No. 112156 | Cat. No. CL09E300MD**
**Description: CL09E300MD Contactor 3-pole 24V 50/60Hz**
**EAN 8425095121560**
**Home > Power devices > Contactors > Series CL - Contactor series for General Purpose application**

Series CL &amp; RL, Three-pole contactor, Terminal: screw, Control Voltage (V): 24V 50/60Hz Max.oper.current AC1 (A):140Max.oper.current AC3 (A):95 Admissible power 220V/230V (kW):25 Admissible power 380V/400V (kW):45



Representative Image

**Descriptors**

Category	Series CL - Contactor series for General Purpose application
----------	--

**Specifications**

Series	Three-pole contactors from 9 to 105 A (AC3)
Control circuit	AC/DC
Terminal type	Double clamp terminal
Non-inductive loads AC1	140 A
Motors = 440V, 3-phase 50/60Hz AC3	95 A
Electrical endurance: # operations AC3	1.7 x 10 <sup>6</sup>
Type	Coil with electronic module for contactors CL - E
Admissible power AC3 220V, 230V	25 kW
Admissible power AC3 380V, 400V	45 kW
Admissible power AC3 415V, 440V	50 kW
Admissible power AC3 500V	55 kW
Package (pcs)	1

**Classifications**

ETIM 5.0	EC000066 - Power contactor, AC switching
ETIM 6.0	EC000066 - Power contactor, AC switching
ETIM 7.0	EC000066 - Power contactor, AC switching

**Dimensions**

Weight	1.440 kg
--------	----------