



Representative Image

Ref. No. 100016 | Cat. No. MCR031ATD
Description: Screw terminal, 3NO+1NC, 24V DC (GE)
EAN 8425095000162
Home > Power devices > Contactors > Series M - Auxiliary Contactors

- Control circuit:
- Direct current up to 250V
- Terminal numbering in accordance with EN 50011
- Fixing system for rapid and simple mounting by clamping onto standard 35mm DIN rail (EN 50022)
- screw and push-on terminals protected against accidental contact in accordance with VDE 0106 T.100, VB94
- Printed circuit version
- Facility to mount instant or timed auxiliary contact blocks and voltage suppressor blocks
- Degree of protection IP20 in accordance with EN60529
- Conform to IEC/EN60947-1, EN/60947-5-1

Descriptors

Category	Series M - Auxiliary Contactors
----------	---------------------------------

Specifications

Series	Auxiliary minicontactors (Ith = 16A)
Control circuit	DC
Terminal	Screw terminal
Control Voltage: DC	24 V
Contacts acc. To EN 50011	3NO+1NC
Number of contacts	4
Utilisation category AC15	110/120V - 6A, 220/240V - 6A, 380/400V - 4A, 415/440V - 4A, 500V - 2.5A, 660/690V - 1.5A
Utilisation category DC13	110V - 1.2A, 220V - 0.6A, 24V - 5A, 440V - 0.25A, 48V - 3.5A
Package (pcs)	10

Classifications

ETIM 5.0	EC000066 - Power contactor, AC switching
ETIM 6.0	EC000066 - Power contactor, AC switching
ETIM 7.0	EC000196 - Contactor relay

Dimensions

Weight	0.210 kg
--------	----------

Publications

Title	Publication No.	Publication Type
4-pole - Auxiliary contactor MC1C-MCRC (stp)		
4-pole - Auxiliary contactor MC1C-MCRC (STEP format)	3D-00067	Drawings - CAD - 3D
4-pole - Auxiliary contactor MC1C-MCRC (pdf)		
4-pole - Auxiliary contactor MC1C-MCRC (3DPDF format)	3D-00067-PDF	Drawings - CAD - 3D

Additional Documentation: Visit our Publication Library to find technical documentation, specifications, articles, promotional literature, 3D's,...