

**Ref. No. 101267 | Cat. No. GPS1MSAL**
**Description: MANUAL MOTOR STARTER MAG.PROT. GPS1 13A STAND.BREAKING**
**EAN 4538915012673**
**Home > Power devices > Manual Motor Starters > Manual motor starter - SURION**


Representative Image

**Descriptors**

Category	Manual motor starter - SURION
----------	-------------------------------

**Specifications**

Series	Surion - GPS1M - Magnetic protection (Ie max 32A)
Rated power 3 phase motors at 220/230Vac Pn (kW)	3 kW
Rated power 3 phase motors at 400Vac Pn (kW)	5.5 kW
Rated power 3 phase motors at 440Vac Pn (kW)	5.5 kW
Rated power 3 phase motors at 500/525Vac Pn (kW)	7.5 kW
Rated current (A)	13 A
Capacity	GPS1MS - Standard breaking capacity
Instantaneous short-circuit release (A)	169 A
Rated ultimate short-circuit breaking cap 220/230V Icu kA	100 kA
Rated ultimate short-circuit breaking cap 400V Icu kA	50 kA
Rated ultimate short-circuit breaking cap 440V Icu kA	50 kA
Rated ultimate short-circuit breaking cap 500/525V Icu kA	42 kA
Rated ultimate short-circuit breaking cap 600V Icu kA	6 kA
Rated ultimate short-circuit breaking cap 690V Icu kA	6 kA
Rated service short-circuit breaking cap 220/230V Ics kA	100 kA
Rated service short-circuit breaking cap 400V Ics kA	38 kA
Rated service short-circuit breaking cap 440V Ics kA	8 kA
Rated service short-circuit breaking cap 500/525V Ics kA	5 kA
Rated service short-circuit breaking cap 600V Ics kA	3 kA
Rated service short-circuit breaking cap 690V Ics kA	3 kA
Pack	5

**Classifications**

ETIM 5.0	EC000074 - Motor protection circuit-breaker
ETIM 6.0	EC000074 - Motor protection circuit-breaker
ETIM 7.0	EC000074 - Motor protection circuit-breaker

## Dimensions

Weight

0.280 kg