

Ref. No. 101211 | Cat. No. GPS1BSAA
Description: MANUAL MOTOR STARTER T+M PROT. GPS1 0,1-0,16A STAND.BREAKING
EAN 8425095012110
Home > Power devices > Manual Motor Starters > Manual motor starter - SURION

Descriptors

Category	Manual motor starter - SURION
----------	-------------------------------

Specifications

Series	Surion - GPS1B - Thermal and magnetic protection (Ie max 32A)
Trip class IEC 60947-4-1	Class 10
Rated power 3 phase motors at 400Vac Pn (kW)	0.02 kW
Rated power 3 phase motors at 440Vac Pn (kW)	0.02 kW
Rated power 3 phase motors at 660/690Vac Pn (kW)	0.06 kW
Rated current (A)	0.16 A
Capacity	GPS1BS - Standard breaking capacity
Thermal current setting range (A)	0.1 - 0.16 A
Instantaneous short-circuit release (A)	2.1 A
Rated ultimate short-circuit breaking cap 220/230V Icu kA	100 kA
Rated ultimate short-circuit breaking cap 400V Icu kA	100 kA
Rated ultimate short-circuit breaking cap 440V Icu kA	100 kA
Rated ultimate short-circuit breaking cap 500/525V Icu kA	100 kA
Rated ultimate short-circuit breaking cap 600V Icu kA	100 kA
Rated ultimate short-circuit breaking cap 690V Icu kA	100 kA
Rated service short-circuit breaking cap 220/230V Ics kA	100 kA
Rated service short-circuit breaking cap 400V Ics kA	100 kA
Rated service short-circuit breaking cap 440V Ics kA	100 kA
Rated service short-circuit breaking cap 500/525V Ics kA	100 kA
Rated service short-circuit breaking cap 600V Ics kA	100 kA
Rated service short-circuit breaking cap 690V Ics kA	100 kA
Pack	5

Classifications

ETIM 5.0	EC000074 - Motor protection circuit-breaker
ETIM 6.0	EC000074 - Motor protection circuit-breaker
ETIM 7.0	EC000074 - Motor protection circuit-breaker

Dimensions

Weight

0.280 kg