



Ref. No. 692793

Description: Miniature circuit breaker UNIBIS EPC 61N 1P+N 1m 6kA C 6A GE

EAN 5413656927938

Home > Modular DIN-rail devices > Circuit Protection > MCB DIN-rail

ElfaPlus Unibis[™]: Quality and reliability guaranteed-High performance clips: To fix the MCB to the DIN rail.-High performance torque: Up to 3Nm.-Easy to replace: Double clips makes it easy to replace the MCB's, especialy when a busbar is installed.-Userfriendly: All screws are on the same level to work fast and easy.-Green or red flag on toggle with isolation applications: Correct information about the real position. Minimum 5mm distance between open contacts is ensured.-Part of the family: Unibis[™] MCB's fit perfectly in the ElfaPlus range.-Safety terminals IP20: The capacity of Unibis[™] terminals has been doubled. Connection possibilities: $2 \times 4mm2$ or $(1 \times 4mm2) + (1 \times 6mm2)$. -Full functionality: A small auxiliary contact is the interface to the complete functionality of the ElfaPlus auxiliaries and accessories.-Saving up to 50% space in distribution boards!

Descriptors

| Category | MCB DIN-rail |
|----------|--------------------|
| Family | Circuit protection |

Specifications

| In (A) | 6 |
|--|--|
| Number of poles | 1P+N |
| Number of modules | 1 |
| Curve Type | C (5-10 ln) |
| Group | ElfaPlus Unibis (compact) |
| Range | Commercial, Residential |
| Switch | EPCN61 : 6kA |
| Connections- Top | Screw |
| Connections- Bottom | Screw |
| Standards | 6kA domestic EN 60898, 7.5kA industrial EN 60947-2 |
| AC/DC | AC |
| Logo | GE |
| Rated voltage | 230 V |
| Short-circuit capacity (kA) | 6 |
| Selectivity class | 3 |
| Terminal capacity max (mm ²) | 10-16 mm ² |
| Electrical service life | 20000/10000 |
| Minimum operating voltage Ubmin (V) | 12 V |
| Terminal capacity min (mm²) | 0.75 / 1 mm² |
| Tropicalisation | 95%RH at 55°C |

Classifications

| Approvals | CE, NF |
|-----------|--|
| ETIM 5.0 | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 6.0 | EC000042 - Miniature circuit breaker (MCB) |



| Classifications | |
|-----------------------|--|
| ETIM 7.0 | EC000042 - Miniature circuit breaker (MCB) |
| | |
| Dimensions | |
| Weight | 0.125 kg |
| | |
| Package Information | |
| Standard packing | 12 |
| | |
| Operating Performance | |
| Operating temperature | -25°C / 55°C |