



Representative Image

Ref. No. 109753 | Cat. No. CL10A300M6

Description: CL10A300M6 Contactor 3-pole 230V 50/60Hz

EAN 8425095097537

Home > Power devices > Contactors > Series CL - Contactor series for General Purpose application

Series CL & RL, Three-pole contactor, Terminal: screw, Control Voltage (V): 230 VAC Max.oper.current AC1 (A): 140 Max.oper.current AC3 (A): 105 Admissible power 220V/230V (kW): 30 Admissible power 380V/400V (kW): 55 Aux.contacts: -

Descriptors

Category	Series CL - Contactor series for General Purpose application
----------	--

Specifications

Series	Three-pole contactors from 9 to 105 A (AC3)
Control circuit	AC
Frequency Control Voltage: AC	50-60 Hz
Terminal type	Double clamp terminal
Non-inductive loads AC1	140 A
Motors = 440V, 3-phase 50/60Hz AC3	105 A
Electrical endurance: # operations AC3	1.5 x 10 ⁶
Type	For contactors type CL - D
Control Voltage: AC	220-230 V
Admissible power AC3 220V, 230V	30 kW
Admissible power AC3 380V, 400V	55 kW
Admissible power AC3 415V, 440V	55 kW
Admissible power AC3 500V	65 kW
Package (pcs)	10

Classifications

ETIM 5.0	EC000066 - Power contactor, AC switching
ETIM 6.0	EC000066 - Power contactor, AC switching
ETIM 7.0	EC000066 - Power contactor, AC switching

Dimensions

Weight	1.440 kg
--------	----------