



Representative Image

**Ref. No. 110645 | Cat. No. CL07A400M6**
**Description: CL07A400M6 Contactor 4-pole 230V 50Hz / 60Hz AC**
**EAN 8425095106451**
**Home > Power devices > Contactors > Series CL - Contactor series for General Purpose application**

Series CL &amp; RL, 4-pole contactor, Terminal: screw, Control Voltage (V): 230 VAC Max.oper.current AC1 (A): 110 Max.oper.current AC3 (A): 65 Admissible power 220V/230V (kW): 42 Admissible power 380V/400V (kW): 72,5 Aux.contacts: -

**Descriptors**

Category	Series CL - Contactor series for General Purpose application
----------	--

**Specifications**

Series	Four-pole contactors from 25 to 140 A (AC1)
Control circuit	AC
Frequency Control Voltage: AC	50-60 Hz
Terminal type	Double clamp terminal
Non-inductive loads AC1	110 A
Motors = 440V, 3-phase 50/60Hz AC3	65 A
Electrical endurance: # operations AC1	1.8 x 10 <sup>6</sup>
Power contacts	4NO
Control Voltage: AC	220-230 V
Admissible power AC1 220V, 230V	42 kW
Admissible power AC1 380V, 400V	72.5 kW
Admissible power AC1 415V, 440V	79 kW
Admissible power AC1 500V	95 kW
Package (pcs)	1

**Classifications**

ETIM 5.0	EC000066 - Power contactor, AC switching
ETIM 6.0	EC000066 - Power contactor, AC switching
ETIM 7.0	EC000066 - Power contactor, AC switching

**Dimensions**

Weight	1.270 kg
--------	----------