


Ref. No. 104474 | Cat. No. CK85BA311N
Description: CK85BA311N Contactor 3P 110V 60Hz
EAN 8425095044746
Home > Power devices > Contactors > Series CK - High efficiency contactors - 825A and 1250A

 Serie CK 3 pole contactors , Control Voltage (V): 220-230V 50Hz / 277V 60Hz Max.oper.current AC1 (A): 315
 Max.oper.current AC3 (A): 205 Admissible power 220V/230V (kW): 65 Admissible power 380V/400V (kW): 110


Representative Image

Descriptors

Category	Series CK - High efficiency contactors - 825A and 1250A
----------	---

Specifications

Series	Three- and four-pole contactors
Control circuit	AC
Frequency Control Voltage: AC	50 Hz, 60 Hz
Range	Three-pole contactors from 150 to 825A (AC3)
Aux Contacts	1NO+1NC
Package (pcs)	1
Motors = 440V, 3-phase 50/60Hz AC3	205 A
Electrical endurance: # operations AC3	1.7 x 10 ⁶
Admissible power AC3 220V, 230V	65 kW
Admissible power AC3 380V, 400V	110 kW
Admissible power AC3 415V	125 kW
Admissible power AC3 440V	125 kW
Admissible power AC3 500V	132 kW

Classifications

ETIM 5.0	EC000066 - Power contactor, AC switching
ETIM 6.0	EC000066 - Power contactor, AC switching
ETIM 7.0	EC000066 - Power contactor, AC switching

Dimensions

Weight	5.900 kg
--------	----------

Publications

Title	Publication No.	Publication Type
CONCK85R CONCK85 Rear view	CONCK85R	Commercial Drawings
CONCK85T CONCK85 Total view	CONCK85T	Commercial Drawings
CONCK85F CONCK85 Front view	CONCK85F	Commercial Drawings
Series CK - Contactor 3-pole CK85B-CK09B-CK95B (stp) 3D Drawing: Controls - Series CK - Contactor 3-pole CK85B-CK09B-CK95B (STEP format)	3D-00010	Drawings - CAD - 3D
Series CK - Contactor 3-pole CK85B-CK09B-CK95B (pdf) 3D PDF Viewer: Controls - Series CK - Contactor 3-pole CK85B-CK09B-CK95B (3DPDF format)	3D-00010-PDF	Drawings - CAD - 3D
CONCK85L CONCK85 Side view	CONCK85L	Commercial Drawings

Additional Documentation: Visit our Publication Library to find technical documentation, specifications, articles, promotional literature, 3D's,...