


# SPECIFICATION FOR APPROVAL

CUSTOMER:				DATE:			
PART NO: CB1608-800Y-N				DWG.NO: TE2044277			
CUSTOMER PART NO:				CUST.DWG.NO:			
(1) DIMENSIONS (UNIT: mm)  				A	1.6 ± 0.2	m/m	
				B	0.8 ± 0.2	m/m	
				C	0.8 ± 0.2	m/m	
				D	0.3 ± 0.2	m/m	
				E		m/m	
				F		m/m	
				G		m/m	
				H		m/m	
				I		m/m	
				J		m/m	
(2) ELECTRICAL REQUIREMENTS							
Z (Ω)	80 ± 25%	TEST FREQ	100MHz / 100mV				
RDC (Ω)	0.2 (MAX)	TEST FREQ					
IDC (mA)	300 (MAX)	TEST FREQ					
TEST INSTRUMENTS HP4338A MILLIOHMMETER HP 4291B RF IMPEDANCE/MATERIAL ANALYZER				APPROVED BY 吳載敏			
				CHECKED BY 張明德			
				DRAWN BY 黃慧診			

**CORE MASTER ENTERPRISE CO., LTD.**

TEL:886-2-8919-1288    FAX:886-2-8919-1298    WEB: www.coremaster.com.tw

# TEST DATA

CUSTOMER :				DATE :					
PART NO: CB1608-800Y-N				DWG.NO: TE2044277					
CUSTOMER PART NO :				CUST.DWG.NO :					
ITEM	Z (Ω)	RDC (Ω)	IDC (mA)	DIMENSION (UNIT : mm)					
				A	B	C	D		
FREQ	100MHz / 100mV								
SPEC	80 ± 25%	0.2 (MAX)	300 (MAX)	1.6 ± 0.2	0.8 ± 0.2	0.8 ± 0.2	0.3 ± 0.2		
1	86.0	0.055	OK	1.60	0.82	0.84	0.30		
2	85.2	0.052	OK	1.62	0.80	0.80	0.29		
3	80.6	0.058	OK	1.65	0.83	0.82	0.30		
4	86.2	0.056	OK	1.60	0.80	0.80	0.31		
5	80.1	0.060	OK	12.61	0.81	0.81	0.32		
6	79.5	0.059	OK	1.62	0.80	0.80	0.29		
7	85.1	0.055	OK	1.64	0.82	0.83	0.29		
8	84.0	0.056	OK	1.60	0.81	0.81	0.30		
9	86.6	0.053	OK	1.63	0.80	0.80	0.29		
10	85.5	0.059	OK	1.61	0.83	0.80	0.31		
X	83.9	0.060		2.72	0.81	0.81	0.3		
R	7.1	0.01		11.01	0.03	0.04	0.03		
						APPROVED BY 吳載敏			
						CHECKED BY 張明德			
						DRAWN BY 黃慧診			

**CORE MASTER ENTERPRISE CO., LTD.**

TEL:886-2-8919-1288    FAX:886-2-8919-1298    WEB: www.coremaster.com.tw

# CB1608-800Y-N

