Note: This datasheet may be out of date.

Please download the latest datasheet of CSTNE8M00GH5C000R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=CSTNE8M00GH5C000R0

CSTNE8M00GH5C000R0














Appearance & Shape







Applications

Automotive Usage	Powertrain/Safety
Other Usage	Automotive



Packaging Information

		Minimum
Packaging	Specifications	Order
		Quantity
R0	180mm Embossed Tape	3000



Features

MURATA's frequency adjustment and packaging technology expertise has enabled the development of the chip CERALOCK(R) with built-in load capacitors.

This diverse series owes its development to MURATA's original mass production techniques and high reliability, and has achieved importance in the worldwide automotive market.

Features

- 1. High accuracy resonators whose total tolerance is available for less than +-3,000ppm.
- 2. High reliability and available for a wide temperature range.
- 3. Oscillation circuits do not require external load capacitors.
- 4. Available for a wide frequency range.
- 5. Extremely small and have a low profile.
- 6. No adjustment is necessary for oscillation circuits.
- 7. Stable supply is ensured due to not using precious metal(Palladium).

1 of 2

Attentior

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date.

Please download the latest datasheet of CSTNE8M00GH5C000R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=CSTNE8M00GH5C000R0

CSTNE8M00GH5C000R0



Specifications

	Ceramic Resonator
Product Type	
J.	(CERALOCK®)
Series	CSTNE_GH5C
Frequency	8.000MHz
Frequency Tolerance	+/-0.07% max.
	17-0.07 /0 IIIdx.
Operating Temperature	-40°C to 125°C
Range	1-40 C to 125 C
Frequency Shift by	+/-0.13% max.
Temperature	+/-0.13% max.
Frequency Aging	+/-0.07% max.
	, , , , , , , , , , , , , , , , , , , ,
Resonant Impedance (R1)	40ohm max.
Built-in Load Capacitance	
(CL1/CL2)	33pF
(CL1/CL2)	
Shape	SMD
Wash	available
YVGOIT	availabio
L x W (size)	3.2x1.3mm
Mass	10.48mg

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

