



SPECIFICATION FOR APPROVAL

File No.: Q/FRK 0.GS.E.C6A-C10

Product Name	AC filter capacitor for PCB
Product Type	C6A
Product Code	C6AU1105KF20452
Customer	
Customer Code	
Issue Date	2020-07

Xiamen Faratronic Co. Ltd.			Approved by Customer
Drafted	Checked	Approved	



Xiamen Faratronic Co. Ltd.

Add: 99 Xinyuan Road, Haicang District, Xiamen, China

Marketing/Sales center

TEL: 0086-592-2335737 6208505 6208586

FAX: 0086-592-6208777


Mail: Vivian@faratronic.com.cn

Donny@faratronic.com.cn

James@faratronic.com.cn

Http: www.faratronic.com.cn

*.The specification are the property of Xiamen Faratronic Co.Ltd and shall not be copied or used as commercial purposes without permission.



Version history





Current version	Date	Author	Change description

AC filter capacitor for PCB





■ Outline Drawing

2 Pins

4 Pins



Square-bottom



Arc-bottom

■ Features


- Self-Healing
- Metallized polypropylene film structure
- Suitable for small power AC filter, i.e. UPS, Solar Photovoltaic DC/AC inverter with LCL filter.

■ Safety Approval

●		TUV Rheinland	EN 61071:2007, EN 61881-1:2011, U_{rms} : 180Vac~500Vac, U_N : 250Vac~700Vac 0.22 μ F~60 μ F, -40/85 $^{\circ}$ C Certificate No.: R 50266136
●		UL/CUL	UL 810, CSA C22.2.No190, Construction Only, Max.660Vac, Max 90 $^{\circ}$ C 证书号(File No.): E256238,CCN:CZDS2/8

■ Specifications

Reference Standard	GB/T 17702, IEC 61071	
Climatic Category	40/85/56	
Max operating Teperature Range(Case)	-40 $^{\circ}$ C ~ +105 $^{\circ}$ C 85 $^{\circ}$ C (+85 $^{\circ}$ C to +105 $^{\circ}$ C: decreasing factor 1.5% per $^{\circ}$ C for U_{rms})	
Rated RMS Voltage (U_{rms})	600Vac	
Rated AC Voltage (U_N)	840Vac	
Maximum continuous DC voltage	900Vdc	
Capacitance Range	1.0 μ F	
Capacitance Tolerance	\pm 10%(K)	
Voltage Proof	Between Terminals:	1.5 U_{rms} (Vac) (10s)
	Between Terminals To Case:	3 000 Vac(60s)
Insulation Resistance(IR \times C $_N$)	\geq 3 000s (20 $^{\circ}$ C, 100V, 1min)	
Dissipation Factor	\leq 20 \times 10 $^{-4}$ (1kHz,20 $^{\circ}$ C)	



■ Part number system

The 18 digits part number is formed as follow:

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18

C	6	A															
---	---	---	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

Digit 1 to 3 Series code

C6A

Digit 4 to 5 Rated RMS Voltage

L4=180V E2=250V Q1=300V U1=600V

Digit 6 to 8 Rated capacitance value

For example: 156=15×10⁶pF=15μF

Digit 9 Capacitance tolerance

J=±5%,K=±10%

Digit 10 Pitch

B=27.5mm F=37.5mm M=52.5mm

Digit 11 Internal use

Digit 12 to 15 Lead form and packaging code

Digit 16 to 18 Internal use

Table 1 lead form and packaging code

Digit 12		Digit 13 and Digit 14		Digit 15	
Code	explanation	Code	explanation	Code	explanation
0	Two pins(bulk)	55	lead length 5.5mm	0	Length tolerance ±1.0mm Or standard length
1	four pins(bulk) P1=10.0mm	45	standard lead length 5.5mm lead length 4.5mm	0 2	Length tolerance ±1.0mm Length tolerance ±0.5mm
2	four pins(bulk) P1=12.7mm				
3	four pins(bulk) P1=20.0mm				
B	four pins(bulk) P1=10.2mm				
A	four pins(bulk) P1=20.3mm				



C6A

■ Technical data(mm)

$U_{rms} = 600Vac$

C_N (μF)	W ± 1.0	H ± 1.0	T ± 1.0	P ± 1.0	P1 ± 0.5	Pins	d ± 0.05	L_s (nH)	ESR @10kHz ($m\Omega$)	\hat{I} (A)	\hat{I} (A)	I_{max} @70°C, 10kHz (A)	Part number
1.0	41.0	33.5	18.5	37.5	-	2	1.0	32	23.0	110	330	4.5	C6AU1105KF20452

■ Caution and warnings

- When using the products shall not exceed the maximum allowed temperature
- Do not apply any mechanical stress to the capacitor terminals
- Do not exceed the specified time or temperature limits during soldering.