



PRODUCT DATA APPROVAL SHEET

Core- I2830


Cosmo Ferrites Ltd. - INDIA

Appearance & Shape: To be free from any defect such as flow, burrs, unevenness etc, As per IEC standards.

Effective Parameters irrespective of material grade (per set)

- Effective Length (L_e): mm
- Effective Area (A_e): mm²
- Effective Area (A_{Min}): mm²
- Effective Volume (V_e): mm³

Approximate Weight: 76g/pc




I2830

Material Grade	Initial Permeability (μ_{iac})	Ordering code
CF139	2100 \pm 20%	CF139 I2830

Dimensions:

Dimension	Nominal (in mm)	Maximum (in mm)	Minimum (in mm)
A	30.0	30.4	29.6
F	28.0	28.4	27.6
G	18.5	18.7	18.3



REMARK: ONLY TWO FACES TO BE GRIND.

For Cosmo Ferrites Limited-INDIA

Checked By: J.C.
 Approved By: B.S.
 Authorized By: KSR
 Date: 09-10-2022 (ISSUE NO.1)

Customer's Approval
 Authorized Signatory:
 Name:
 Date:

NOTE: Please send this Data Sheet back to Cosmo Ferrites Ltd. after approval. If not received back within 15 days, it will be presumed that all the specifications given in the consent/data sheet are acceptable to the concerned.