



Material: UL NYLON 66 (natural color/black)
 Fire rating 94V-2

Product usage: PCB , plate , Good for
 computer or electronics equipment fixation
 Characteristic: For better insulation, light
 weight. No rust

GENERAL TOLERANCE	PROJECTION		Description:
.X. ±0.50	UNITS	mm	Pan Head Screws
.X ±0.25	SCALE	1:1	
.XX ±0.10	Draw by:	Jenny	
ANGLE TOLERANCE	Check by:		KLS P/N: L-KLS8-0318-NF
.X. ±5°	Date	2018-03-01	NingBo KLS ELECTRONIC CO.,L TD.
.X ±3°	SHEET	1 OF 1	
.XX ±2°			

Item No.		A	B	C	D	Pitch	Packing
Nylon							
Natural color	Black						
L-KLS8-0318-NF-M2-05	L-KLS8-0318-NF-M2-05B	2.0	5	1.4	3.5	0.4	1000PCS
L-KLS8-0318-NF-M2-06	L-KLS8-0318-NF-M2-06B		6				
L-KLS8-0318-NF-M2-08	L-KLS8-0318-NF-M2-08B		8				
L-KLS8-0318-NF-M2-10	L-KLS8-0318-NF-M2-10B		10				
L-KLS8-0318-NF-M2.5-06	L-KLS8-0318-NF-M2.5-06B	2.5	6	2.0	4.5	0.45	
L-KLS8-0318-NF-M2.5-08	L-KLS8-0318-NF-M2.5-08B		8				
L-KLS8-0318-NF-M2.5-10	L-KLS8-0318-NF-M2.5-10B		10				
L-KLS8-0318-NF-M3-04	L-KLS8-0318-NF-M3-04B	3.0	4	2.5	5.6	0.5	
L-KLS8-0318-NF-M3-06	L-KLS8-0318-NF-M3-06B		6				
L-KLS8-0318-NF-M3-08	L-KLS8-0318-NF-M3-08B		8				
L-KLS8-0318-NF-M3-10	L-KLS8-0318-NF-M3-10B		10				
L-KLS8-0318-NF-M3-12	L-KLS8-0318-NF-M3-12B		12				
L-KLS8-0318-NF-M3-15	L-KLS8-0318-NF-M3-15B		15				
L-KLS8-0318-NF-M3-20	L-KLS8-0318-NF-M3-20B		20				
L-KLS8-0318-NF-M3-22	L-KLS8-0318-NF-M3-22B		22				
L-KLS8-0318-NF-M3-25	L-KLS8-0318-NF-M3-25B	25					
L-KLS8-0318-NF-M4-06	L-KLS8-0318-NF-M4-06B	4.0	6	2.8	7.0	0.7	
L-KLS8-0318-NF-M4-08	L-KLS8-0318-NF-M4-08B		8				
L-KLS8-0318-NF-M4-10	L-KLS8-0318-NF-M4-10B		10				
L-KLS8-0318-NF-M4-12	L-KLS8-0318-NF-M4-12B		12				
L-KLS8-0318-NF-M4-15	L-KLS8-0318-NF-M4-15B		15				
L-KLS8-0318-NF-M4-20	L-KLS8-0318-NF-M4-20B		20				
L-KLS8-0318-NF-M4-25	L-KLS8-0318-NF-M4-25B		25				
L-KLS8-0318-NF-M4-30	L-KLS8-0318-NF-M4-30B		30				
L-KLS8-0318-NF-M4-45	L-KLS8-0318-NF-M4-45B		45				

Item No.		A	B	C	D	Pitch	Packing
Nylon							
Natural color	Black						
L-KLS8-0318-NF-M5-08	L-KLS8-0318-NF-M5-08B	5.0	8	3	9.0	0.8	1000PCS
L-KLS8-0318-NF-M5-10	L-KLS8-0318-NF-M5-10B		10				
L-KLS8-0318-NF-M5-12	L-KLS8-0318-NF-M5-12B		12				
L-KLS8-0318-NF-M5-15	L-KLS8-0318-NF-M5-15B		15				
L-KLS8-0318-NF-M5-20	L-KLS8-0318-NF-M5-20B		20				
L-KLS8-0318-NF-M5-25	L-KLS8-0318-NF-M5-25B		25				
L-KLS8-0318-NF-M5-30	L-KLS8-0318-NF-M5-30B		30				
L-KLS8-0318-NF-M5-40	L-KLS8-0318-NF-M5-40B		40				
L-KLS8-0318-NF-M6-10	L-KLS8-0318-NF-M6-10B	6.0	10	3.5	10.0	1.0	
L-KLS8-0318-NF-M6-12	L-KLS8-0318-NF-M6-12B		12				
L-KLS8-0318-NF-M6-15	L-KLS8-0318-NF-M6-15B		15				
L-KLS8-0318-NF-M6-20	L-KLS8-0318-NF-M6-20B		20				
L-KLS8-0318-NF-M6-25	L-KLS8-0318-NF-M6-25B		25				
L-KLS8-0318-NF-M6-30	L-KLS8-0318-NF-M6-30B		30				
L-KLS8-0318-NF-M6-35	L-KLS8-0318-NF-M6-35B		35				
L-KLS8-0318-NF-M6-40	L-KLS8-0318-NF-M6-40B		40				
L-KLS8-0318-NF-M8-12	L-KLS8-0318-NF-M8-12B	8.0	12	5	14.0	1.25	
L-KLS8-0318-NF-M8-15	L-KLS8-0318-NF-M8-15B		15				
L-KLS8-0318-NF-M8-20	L-KLS8-0318-NF-M8-20B		20				
L-KLS8-0318-NF-M8-25	L-KLS8-0318-NF-M8-25B		25				
L-KLS8-0318-NF-M8-30	L-KLS8-0318-NF-M8-30B		30				
L-KLS8-0318-NF-M8-40	L-KLS8-0318-NF-M8-40B		40				