PIN HEADER 2.54mm (Single Row)



2.54mm单排针

材 质 Material:

绝缘体 Insulator: Glass filled PBT UL94V-0 ,Black
接触件 Contacts: Brass
电镀层 Plating: Whole Gold plated over Nickel

电气性能 Electrical Characteristics:

接触电阻 Contact Resistance: 30mΩmax. at DC 100mA
绝缘电阻 Insulator Resistance: 1000MΩmin. at 500V DC
耐压 Withstanding Voltage: 1000V AC/rms 50Hz For 1 minute
工作电流 Current Rating: 2 AMP
使用温度范围 Operating Temperature: -40℃~+105℃
焊接温度 Soldering Temperature:260℃,6s max

订购方法 How To Order

DK501 - 1x40	S	B	G
Series / Position	S: Straight R: Right Angle M: S.M.T	B: Black Y: Grey	G: Gold Plated T: Tin Plated

常规表达：型号（单排针）-规格（01~40）-类型（S或R）

针脚长度(L) 可以选择 L1:Dip Length / L2:Mating Length / L3:Extended Length

*其它要求的产品另外说明 Other requests 's product on the other hand description

Straight Type



Surface Mount Type



Right Angle Type







R1 TYPE



R2 TYPE



P.C.B Layout

Position / Dimension	1 Thru 40
A ± 0.20	2.54 X No.of Positions
B ± 0.15	2.54 X No.of Positions -2.54