



SPECIFICATION FOR APPROVAL

CUSTOMER:		DATE:
PART NO: RC0810U-152K		DWG.NO: HX4006884
CUSTOMER PART NO:		CUST.DWG.NO:
(1) DIMENSION(UNIT: mm) 		A 10.0 (MAX) m/m
		B 12.0 (MAX) m/m
		C 15.0 ± 2.0 m/m
		D 5.0 (REF) m/m
		E 0.65 (REF) m/m
		F m/m
		G m/m
		H m/m
		(2)ELECTRICAL REQUIREMENTS
L (mH)	1.5 ± 10%	
RDC (Ω)	3.0 (MAX)	
IDC (A)	0.6 (MAX)	
TEST CONDITION	1KHz / 0.25V	
(4)MATERIAL LIST		
NO/ITEM	MATERIAL	SUPPLIER
CORE	DR2W 8×10 或同等級	SUMER
WIRE TYPE	2UEW φ 0.2mm 或同等級	TAIYI
WINDING	220TS (REF)	
TUBE	黑色 UL 8×12mm 或同等級	STARS
		APPROVED BY 吳載敏
		CHECKED BY 張明德
		DRAWN BY 黃慧診

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw

TEST DATA

CUSTOMER:				DATE:				
PART NO: RC0810U-152K				DWG.NO: HX4006884				
CUSTOMER PART NO :				CUST.DWG.NO :				
TEST CONDITION: 1KHz / 0.25V				DIMENSION (UNIT : mm)				
ITEM	L (mH)	RDC (Ω)	IDC (A)	A	B	C	D	E
SPEC	1.5 ± 10%	3.0 (MAX)	0.6 (MAX)	10 (MAX)	12 (MAX)	15 ± 2.0	5.0 (REF)	0.65 (REF)
1	1.410	1.91	OK	8.84	10.88	14.67	5.02	0.65
2	1.420	1.93	OK	8.79	10.82	14.80	5.01	0.64
3	1.403	1.96	OK	8.82	10.90	14.79	5.02	0.64
4	1.419	1.96	OK	8.86	10.88	14.75	5.01	0.65
5	1.404	1.93	OK	8.79	10.89	14.75	5.04	0.64
6	1.424	1.95	OK	8.76	10.79	14.62	4.96	0.65
7	1.397	1.94	OK	8.82	10.86	14.75	5.02	0.64
8	1.433	1.95	OK	8.89	10.80	14.80	5.01	0.64
9	1.398	1.93	OK	8.84	10.91	14.73	5.02	0.64
10	1.312	1.94	OK	8.79	10.87	14.78	5.03	0.65
X	1.402	1.94		8.82	10.86	14.74	5.01	0.64
R	0.121	0.05		0.13	0.12	0.18	0.08	0.01
TEST INSTRUMENTS HM2791 METER FOR L						APPROVED BY 吳載敏		
						CHECKED BY 張明德		
						DRAWN BY 黃慧診		

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw