



Representative Image

Ref. No. 104053 | Cat. No. CL00A310TJ

Description: CL00A310TJ Contactor 3-pole 110V 50Hz AC

EAN 8017018040531

Home > Power devices > Contactors > Series CL - Contactor series for General Purpose application

Series CL & RL, Three-pole contactor, Terminal: screw, Control Voltage (V): 110V 50Hz AC Max.oper.current AC1 (A):25 Max.oper.current AC3 (A):9 Admissible power 220V/230V (kW):2.2 Admissible power 380V/400V (kW):4 Aux.contacts:1NO

Descriptors	
Category	Series CL - Contactor series for General Purpose application

Specifications

Series	Three-pole contactors from 9 to 105 A (AC3)
Control circuit	AC
Frequency Control Voltage: AC	60 Hz 50-60 Hz
Range	CL Contactors
Terminal type	Screw terminal
Non-inductive loads AC1	25 A
Motors = 440V, 3-phase 50/60Hz AC3	9 A
Electrical endurance: # operations AC3	2 x 10 ⁶
Aux Contacts	1NO
Power contacts	3NO
Control Voltage: AC	110 V
Admissible power AC3 220V, 230V	2.2 kW
Admissible power AC3 380V, 400V	4 kW
Admissible power AC3 415V, 440V	4 kW
Admissible power AC3 500V	5.5 kW

Classifications

ETIM 6.0	EC000066 - Power contactor, AC switching
ETIM 7.0	EC000066 - Power contactor, AC switching



Publication No.	Publication Type
CONACL00L	Commercial Drawings
CONACL00R	Commercial Drawings
CONACL00T	Commercial Drawings
CONACL00F	Commercial Drawings
	CONACLOOL CONACLOOR CONACLOOT

Additional Documentation: Visit our Publication Library to find technical documentation, specifications, articles, promotional literature, 3D's,...