



SPI 2813 60Led/m LED STRIP

Description

DC5V input WS2813 LED Strip is new Digital LED Light, the circuits can Dual-signal wires version, signal break-point continuous transmission. If one LED is damaged, the following LEDs can still work. It can realize various colorful changing patterns with corresponding controller. You can control the brightness and the color of each LED individually, which allows you to produce amazing and complex effects in a simple way. It has 60 pcs led per meter, and 60 pixels per meter.



Specifications

Product Photometrics

| | | | |
|-----------------------------|-----------------------|---------------------------|--------------------------|
| LED Type | 5050(2813) SMD | Input Voltage | 5V |
| LED Brightness | 2000-2400MCD | Peak Power (w/m) | 10w/m |
| LED Density | 60 pcs/m | Energy consumption | 6 Kwh/1000h |
| Pixel Point Quantity | 60 pcs /m | Energy class | A+ |
| Cutable Segments | 1 Leds/16.7 mm | Ra | --- |
| PCB Type/Color | 3 OZ, White/Black PCB | IP Grade | IP20/IP54/IP65/IP67/IP68 |
| PCB Width | 10 mm | Warranty | 3 Years |
| Reel Length | 5 m | Certification | UL CE RoHS |

| SKU | Model No | LED Density | Work Voltage | Peak Power | Color | Brightness |
|-------|-------------------------|-------------|--------------|------------|-------|------------|
| 29415 | S2813-60-RGB-V5-NWP-P10 | 60 led/m | DC 5V | 10 w/m | RGB | --- |

Packing Information

Standard Packing Per Bag

5 meters/reel, 1 reel/anti-static bag
G.W. : Non-waterproof-0.12KG

Standard Packing Per Outer Carton

25 bags to 1 inner box, size : 34x20x22 cm
4 inner boxes to 1 outer carton size: 42x35x46cm

NOTES:

1. LED Strip maintains a tester tolerance of $\pm 5\%$ on Color Temperature and Lumen , tolerance of ± 3 on CRI-Ra.
2. The test is based on our laboratory and testing equipment.
3. We reserve the right to modify and improve the design of our fixtures without prior notice.