

File No. (文件编号): L-KLS7-SS-24N02-G4.2

Prepared(编制): 何国豪

Date(日期) : 2018. 3. 17

Page(页数) : 1 of 1

Approved(批准): 殷连杰

1. Specifications:

- 1) Rating(标称) : 12R(2)A 125/250VAC 25T105
- 2) Function(功能) : DP 4T
- 3) Operation force(推力) : 300gf~800gf
- 4) Insulation resistance(绝缘电阻): 100M Ω
- 5) Dielectric withstand(耐压)
Ter. And Ter. : 1500V/100mA/min(Before endurance)
: 1125V/100mA/min(After endurance)
Ter. And Knob : 3000V/100mA/min(Before endurance)
: 2250V/100mA/min(After endurance)
- 6) Contact resistance(接触电阻) : 50m Ω Max.
- 7) Temperature Rise(温升) : 45 $^{\circ}$ C Max. (Before endurance)
: 30 $^{\circ}$ C Max. (6KC)
: 55 $^{\circ}$ C Max. (After endurance)
- 8) Operating Life(电气寿命) : 10000 Cycles

- 1) Rating(标称) : 8A 250VAC 25T105(EN61058-1)
- 2) Function(功能) : DP 4T
- 3) Operation force(推力) : 300gf~800gf
- 4) Insulation resistance(绝缘电阻): 100M Ω
- 5) Dielectric withstand(耐压)
Ter. And Ter. : 1500V/10mA/5s(Before endurance)
: 1125V/10mA/5s(After endurance)
Ter. And Knob : 3000V/10mA/5s(Before endurance)
: 2250V/10mA/5s(After endurance)
- 6) Contact resistance(接触电阻) : 50m Ω Max.
- 7) Temperature Rise(温升) : 45 $^{\circ}$ C Max. (Before endurance)
: 55 $^{\circ}$ C Max. (After endurance)
- 8) Operating Life(电气寿命) : 10000 Cycles

2. Remark(备注)

- 1) RoHS Reach