

TERMO ANEMOMETRE



CFM/CMM Thermo-Anemometer with built-in non-contact IR Thermometer measures remote surface temperature to 280°C (536°F) and 8:1 distance to spot ratio.

Multifunction Air Velocity Meter with wide temperature range (618/618B)

CFM/CMM Thermo-Anemometer (619)

CFM/CMM Thermo-Anemometer + InfraRed Thermometer

Max/Min/Avg value with relative time stamp

Low battery indication and Auto Power Off

Display Air Flow (CFM/CMM), or Air Velocity plus Temperature simultaneously

Air Velocity	Range	Accuracy	619
m/s(meter per second)	0.40~30.00	±3% ±0.20m/s	*
ft/min(feet per minute)	80~5900	±3% ±40ft/min	*
km/h(kilometers per hour)	1.4~108.0	±3% ±0.8km/h	*
MPH(miles per hour)	0.9~67.0	±3% ±0.4MPH	*
Knots(nautical miles per hour)	0.8~58.0	±3% ±0.4knots	*
Air Temperature	-10-60°C(14-140°F)	± 2.0°C(4.0°F)	*
InfraRed Temperature	-50 to -20°C(-58 to -4°F)	± 5.0°C(9.0°F)	
	-20 to 260°C(-4 to 500°F)	±2% reading or ± 2°C(4°F)	
Air Flow	Range	Area	
CFM	0-999900	0-999.9 ft²	*
CMM	0-999900	0-999.9 m²	*

