

**OPA-AR**

( Home : Products : Sw itches : MICRO SWITCH™ Limit Sw itches : MICRO SWITCH™ Global Limit Sw itches : OP )



**Enclosed Switch Series OP: Side Rotary, Fixed lever length with steel roller, 1NO 1NC Snap Action SPDT, CW actuation, High capacity**

Actual product appearance may vary.

**Product Specifications**

|                                |  |
|--------------------------------|--|
| Availability                   | Global   |
| Operating Force (OF)           | 3,34 N to 8,90 N [12 oz to 32 oz]  |
| Release Force                  | 35,59 N [8 oz] min.  |
| Pretravel (PT)                 | 5,56 mm [0.219 in] max.  |
| Overtravel (OT)                | 25°  |
| Differential Travel (DT)       | 0,3 mm [0.012 in] max.   |
| Product Type                   | Enclosed Sw itches   |
| Actuator                       | Side Rotary  |
| Lever Type                     | 1.5 in Fixed Length Lever w ith back mounted Steel Roller (.75 in dia. x .25 in w ide)   |
| Circuitry                      | 1NC 1NO Snap Action, SPDT  |
| Ampere Rating                  | 20 A   |
| Supply Voltage                 | 125 Vac, 250 Vac, 480 Vac  |
| Housing Material               | Aluminum Die-Cast  |
| Termination Type               | 0.5 in - 14NPT Conduit   |
| Series Name                    | OP   |
| Sealing                        | NEMA 1, 3, 4, 13   |
| UL File #                      | E12252   |
| Comment                        | CW actuation. High capacity. Field adjustable through 360 degrees. Roller lever may be positively locked at intervals of approx. 0.2 degrees |
| Agency Approvals and Standards | UL, CSA  |
| UNSPSC Code                    | 39122213   |
| UNSPSC Commodity               | 39122213 Limit Sw itches   |