

# DLMONSN900HY2#


In Production RoHS REACH

< List of part numbers with package codes > DLM0NSN900HY2B DLM0NSN900HY2D



## Appearance & Shape





## Applications

Limited Usage	For differential signal interface line
Other Usage	For general

Note: This datasheet may be out of date. Please download the latest datasheet of DLM0NSN900HY2# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=DLM0NSN900HY2%23

### "#" indicates a package specification code.

Pa

## Packaging Information

	Packaging	Specifications	Standard Packing
ľ	В	Bulk(Bag)	Quantity 500
	D	180mm Paper Tape	10000



## Features

- 1. Small size and tight dimensional tolerance Size:0.85x0.65x0.45mm Tolerance:+-0.05mm
- 2. High common mode impedance up to 90ohm (at 100MHz) is available.
- 3. DLMONSN series enables noise suppression for differential signal line without distortion in highspeed signal transmission due to its line impedance matching.
- 4. High Cut-off Frequency.

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# DLMONSN900HY2#

Note: This datasheet may be out of date. Please download the latest datasheet of DLM0NSN900HY2# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=DLM0NSN900HY2%23

### "#" indicates a package specification code.



## Specifications

Brand Murata

Shape	SMD	
Size Code (in mm)	0806	
Size Code (in inch)	03025	
Length	0.85mm	
Length Tolerance	±0.05mm	
Width	0.65mm	
Width Tolerance	±0.05mm	
Thickness	0.45mm	
Thickness Tolerance	±0.05mm	
Common Mode Impedance (at 100MHz)	90Ω	
Common Mode Impedance (at 100MHz) Tolerance	±25%	
Rated Current	100mA	
Derating of Rated Current	No	
Rated Voltage	5Vdc	
Withstanding Voltage	12.5Vdc	
DC Resistance(max.)	5Ω	
DC Resistance	4.0Ω±25%	
Insulation Resistance(min.)	10ΜΩ	
Cut-off Frequency	2.0GHz (Typ.)	
Operating Temperature Range	-40°C to 85°C	
Mass(typ.)	0.9mg	
Number of Circuit	1	
Operating Temperature Range(Self-temperature rise is included)	No	

2	∩f	3
_		0

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.








DLMONSN900HY2#


Note: This datasheet may be out of date. Please download the latest datasheet of DLM0NSN900HY2# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=DLM0NSN900HY2%23

### "#" indicates a package specification code.







Impedance-Frequency Characteristics

Impedance-Frequency Characteristics (Main Items)


000

000

No Polarity.

 $(1) \bigcirc$ 

(4) C



Differential Mode Transmission Characteristics (Typical Value)

Equivalent Circuit

(2)

O (3)

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



without advance notice. Please check with our sales representatives or product engineers before ordering.

<sup>2.</sup> This datasheet has only typical specifications because there is no space for detailed specifications.