

# DLW32SH510XK2#

Note: This datasheet may be out of date.

Please download the latest datasheet of DLW32SH510XK2# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=DLW32SH510XK2%23

"#" indicates a package specification code.

For CAN/CAN-FD DCMR Class2 Compliance










< List of part numbers with package codes > DLW32SH510XK2L DLW32SH510XK2B



## Appearance & Shape







Automotive Usage

Powertrain/Safety



## Packaging Information

Packaging	Specifications	Standard Packing Quantity
В	Bulk(Bag)	500
L	180mm Embossed Tape	1500



## **Features**

1. Suitable for noise suppression at car area networks like CAN/CAN-FD

(IEC62228-3 DCMR Class2 Compliance)

- 2. High common mode impedance at high frequency range. So it is suitable for noise suppression through wide frequency
- 3. Wide operating temperature range (-40 to +125 degrees C)

### **Applications**

Common mode noise suppression for car area networks like CAN/CAN-FD.

1 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





### Please download the latest datasheet of DLW32SH510XK2# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=DLW32SH510XK2%23

Note: This datasheet may be out of date.

"#" indicates a package specification code.



# **Specifications**

DLW32SH510XK2#

Shape	SMD	
Size Code (in mm)	3225	
Size Code (in inch)	1210	
Length	3.2mm	
Length Tolerance	±0.2mm	
Width	2.5mm	
Width Tolerance	±0.2mm	
Thickness	2.35mm	
Thickness Tolerance	±0.15mm	
Rated Current	200mA	
Derating of Rated Current	No	
Rated Voltage	80Vdc	
Withstanding Voltage	200Vdc	
DC Resistance(max.)	0.7Ω	
DC Resistance	0.7Ω max.	
Insulation Resistance(min.)	10ΜΩ	
Operating Temperature Range	-40°C to 125°C	
Mass(typ.)	0.072g	
Number of Circuit	1	
Common Mode Inductance	51μH-30%/+50% (at 0.1MHz)	
Operating Temperature Range(Self-temperature rise is included)	No	
Brand	Murata	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



# DLW32SH510XK2#


Note: This datasheet may be out of date.


Please download the latest datasheet of DLW32SH510XK2# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=DLW32SH510XK2%23

"#" indicates a package specification code.








Impedance-Frequency Characteristics

Impedance-Frequency Characteristics (Main Items)



**Equivalent Circuit** 

3 of 3

### Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

