

Product Search Data Sile

Note: This datasheet may be out of date.

Please download the latest datasheet of NFE31ZT222Z1E9# from the official website of Murata Manufacturing Co., Ltd.

Packaging Information

330mm Embossed Tape

180mm Embossed Tape

Specifications

Bulk(Bag)

http://www.murata.com/en-gb/products/productdetail?partno=NFE31ZT222Z1E9%23

"#" indicates a package specification code.

NFE31ZT222Z1E9#









< List of part numbers with package codes >

NFE31ZT222Z1E9B


NFE31ZT222Z1E9K

NFE31ZT222Z1E9L



Appearance & Shape







: Electrode

Packaging

В

Κ

L

Features

The chip "EMIFIL" NFE31ZT is a small size T-type circuit EMI suppression filter.

Features

- Its large rated current of 6A and low voltage drop due to small DC resistance are suitable for DC power line use.
- 2. The feedthrough capacitor realizes excellent high frequency characteristics.
- 3. The structure incorporates built-in ferrite beads which minimize resonance with surrounding circuits.
- 4. 22 to 2,200pF lineups can be used in signal lines.

Applications

Automotive Usage

Infotainment

1 of 3

Standard

Packing

Quantity

500

8000

2000

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





NFE31ZT222Z1E9#

Note: This datasheet may be out of date.

Please download the latest datasheet of NFE31ZT222Z1E9# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=NFE31ZT222Z1E9%23

"#" indicates a package specification code.



Specifications

Shape	SMD
Size Code (in inch)	1206
Length	3.2mm
Length Tolerance	±0.35mm
Width	1.6mm
Width Tolerance	±0.15mm
Thickness	1.6mm
Thickness Tolerance	±0.15mm
Operating Temperature Range	-40°C to 85°C
Mass(typ.)	0.034g
Number of Circuit	1
Rated Current	6A
Rated Voltage	25Vdc
Withstanding Voltage	62.5Vdc
Insulation Resistance(min.)	1000ΜΩ
Capacitance	2200pF
Capacitance Tolerance	±50%
Size Code (in mm)	3216

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Manufacturing Co., Ltd.

 $Please\ download\ the\ latest\ data sheet\ of\ NFE 31ZT 222Z 1E9\#\ from\ the\ official\ website\ of\ Murata$

http://www.murata.com/en-gb/products/productdetail?partno=NFE31ZT222Z1E9%23


Note: This datasheet may be out of date.


"#" indicates a package specification code.

NFE31ZT222Z1E9#




Product Data





Insertion Loss Characteristics

Insertion Loss Characteristics (Main Items)



Equivalent Circuit

3 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

