

VFS6VD81E221T51#

Note: This datasheet may be out of date.

Please download the latest datasheet of VFS6VD81E221T51# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=VFS6VD81E221T51%23

"#" indicates a package specification code.

Discontinued






< List of part numbers with package codes > VFS6VD81E221T51B



Appearance & Shape







Features

VFS6V series is designed for surge protection of signal line. It protects electric circuit from surges such as static electricity and suppresses EMI noise. Built-in ferrite bead gives excellent EMI suppression.

Applications

Elimination of noise and protection of electric circuits in office equipment, including computers and peripheral equipment, copy machines, and communication terminals.



Applications

Other Usage For general



Packaging Information

Packaging	Specifications	Standard Packing Quantity
В	Bulk(Bag)	250

1 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





VFS6VD81E221T51#

Note: This datasheet may be out of date.

Please download the latest datasheet of VFS6VD81E221T51# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=VFS6VD81E221T51%23

"#" indicates a package specification code.



Specifications

Shape	Lead
Length	8.0mm
Length Tolerance	max.
Width	2.54mm
Width Tolerance	max.
Thickness	10.5mm
Thickness Tolerance	max.
Rated Current	6A
Operating Temperature Range	-40°C to 105°C
Mass(typ.)	0.48g
Rated Voltage	25Vdc
Varistor Voltage	50Vdc
Varistor Voltage Torelance	±20%
Capacitance	220pF
Capacitance Tolerance	±20%
Peak Pulse Current	100A

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



VFS6VD81E221T51#


Note: This datasheet may be out of date.


Please download the latest datasheet of VFS6VD81E221T51# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=VFS6VD81E221T51%23

"#" indicates a package specification code.







Insertion Loss Characteristics

Equivalent Circuit

3 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

