

ORDER INFORMATION:

KLS17-AFC-08-28AWG-1.5-R-1

08: 02-08pin

28AWG: or 26AWG

pitch:1.25mm or 1.5mm

R: Red L: Blue

Length /Reel: 1-30.5M/Reel 2-76.5M/Reel 3-153M/Reel 4-305M/Reel

UL20080 PVC FLAT WIRE

Product Category: PVC FLAT CABLE

Temperature Rating: 80°C

Rated voltage: 30V

Test voltage: 2000V

Insulation Material: PVC

Conductor material: bare copper/tinned copper/sliver copper

Application: For internal wiring of electronic and electrical equipment

Conductor			Insulates				Electrical specification	Packs	Packs
AWG	Conductor NO*mm	Diameter mm	The core counts	Thick mm	Spacing	Over diameter mm	Max.resistance at 20°C(Ω /KM)	Standing voltage	Meter/Roll
28	19*0.08	0.40	AFC-02	0.41	1.22	2.54	239	500	305
			AFC-03			3.86			
			AFC-04			5.18			
			AFC-05			6.50			
			AFC-06			7.82			
			AFC-07			9.14			
			AFC-08			10.46			
26	30*0.08	0.51	AFC-02	0.41	1.33	2.76	150	500	305
			AFC-03			4.19			
			AFC-04			5.62			
			AFC-05			7.05			
			AFC-06			8.48			
			AFC-07			9.91			
			AFC-08			11.34			

Package:

TYPE 1: 30.5 M

TYPE 2: 76.5 M

TYPE 3: 153 M

TYPE 4: 305 M