## **PZ-58**






## Multi-purpose Extraction Tool for stubborn fasteners. Stripped or Rusted screws -- Just Grip & Turn with PZ-58 !!

• Unique jaws with both vertical and horizontal serrations grip a screw head securely without slipping

Features

- Slim jaws designed for work in confined areas
- Much faster than fluted screw extractor and simpler than vise grip pliers
- With a side cutter for wire cut
- Spring loaded for fatigue-free work
- Internationally awarded design



=Pan head screw= PZ-58 has a firm grip on the screw head.



head. Ultimate bite!

Cut copper wire (dia. 1.2mm) or steel wire (dia. 1.0mm)



Fatigue-free owing to spring action

## Heavy-duty T-shaped handles



This unique handle shape helps to prevent the handle sleeve from twisting or turning round, good for heavy users.

Light weight (20% less in-house comparison)

Screw Head Size



Dome (Truss) Head Round or Pan Head Screw head: dia. 3 to 9.5mm

## Applications









Home improvement Do-It-Yourself

How does PZ-58 work?



Automobile maintenance



Repair work

Ordinary Pliers

Note

ma puntanno

 The tool may not remove speciallyhardened, heat-treated or glued screws.
Be sure to apply this tool to a screw head, but not to screw thread.



Ordinary pliers jaws are lined with horizontal serrations. When you grasp and turn a screw head with ordinary pliers, the jaws slip and the screw remains stuck.



The tips of jaws can not reach the outer edge of screw head when the jaws are opened.

(hinte



Specially-designed teeth generate gripping power.



The serrated jaws angled inward grab the rim of screw head, so no slippage.


**Related Products** 

PZ-58



Pliers Mask for PZ-58 (PZM-58)

Specifications



| Item No. | Size  | Material                           | Hardness | Screw Head Size | Cutting Capacity            | Weight |
|----------|-------|------------------------------------|----------|-----------------|-----------------------------|--------|
| PZ-58    | 160mm | Body: Carbon Steel<br>Handles: TPR | HRC58±2  | dia. 3 to 9.5mm | dia. 1.2mm<br>(Copper Wire) | 130g   |