PZ-79









With unique non-slip gripping jaws, a must for electricians

- Cuts PVC insulated 3-core wire easily with one hand.
- Well-structed and durable shears
- Crimper for bare terminals (AWG16~12)
- Cross-hatched jaws to hold a thin plate, tie band and other parts securely without slippage
- With unique screw extractor owing to vertical serrations inside the jaws

Shears-structed cable cutter (Comparison)



PZ-79: Fine cutting in finish owing to shears structure

2-way non-slip gripping jaws





Screw Remover 3.5mm offset vertical serrations

Cross-hatched pattern Gripping with no slip

- Vertical serrations to grip a screw head securelyCross-hatch to hold a tie band and a thin plate

Removable Screws







Torx



Stripped Rusted

Dome Head

Dome (Truss) Head Round or Pan Head Screw head: dia. 3 to 9.5mm


Note





- 1) The tool may not remove specially-hardened, heat-treated or glued screws.
- 2) Be sure to apply this tool to a screw head, but not to screw

Specifications



Item no.	Size	Blade Length	Material	Jaws Hardness	Screw Head Size
PZ-79	215mm	20mm	Body: Carbon Steel Handles: PVC	HRC60±2	dia. 3 to 9.5mm

Cutting Capacity (Copper Wire)	Crimper	Weight
dia. 2.6mm x 3 cores (Flat cable) dia. 5.5mm x 3 cores (Round cable)	1.25~3.5mm2 (for bare terminals)	340g