

PERFWIPE ESD Container with Lid Specification

Descriptions:

ESD Containers with Lids are manufacture from conductive plastic material PP , Made of reinforced thermoset composite material,

ESD Containers with Lids are ideal for transport and storage of electronically sensitive products

Equipped with a fixed hinged lid and plastic locking levers

Extra reinforced corners to increase structural integrity, impact resistance and stacking load

Compatible with other stacking bins, roll cages and transport dollies and pallets

these boxes offer permanent ESD protection without requiring surface treatment

Features:

Special passage resistance / surface resistance: $10^6 < 10^{10}$ Ohm/cm

Made of new raw material PP copolymer

Resistant to extreme cold and heat from -20°C to +90°C(temperature range of -60 degrees F to 250 degrees F.)

Suitable for automatic high bay warehouses and roller conveyors

All ESD Containers with Lids products are dimensionally stable, withstand static loads greater than 200 lbs.

Application:

ESD container with lids provide effective protection for handling PC boards and electronic components in assembly, packaging, storage and processing areas.

Ideal for storage, transport and handling of electronic components

Order Informations:

Model Number	External Size(mm)	Internal Size(mm)	Lids size(mm)
SSC3020	600x500x360	560x460x355	610x505x15
SSC3020A	600x500x400	560x460x395	610x505x15
SSC3023	600x500x150	560x460x140	610x505x15
SSC3024	600x500x300	560x460x290	610x505x15
SSC3026A	600x500x160	560x460x155	610x505x15
SSC3018	565x420x240	510x390x235	566x427x15
SSC3019	565x420x300	510x390x290	566x427x15
SSC3019A	565x420x380	510x390x375	566x427x15
SSC3017	500x360x175	440x320x165	484x357x14
SSC3017C	480x355x220	430x305x210	484x357x14
SSC3017D	476x352x320	430x305x315	484x357x14
SSC3019B	620x425x320	580x395x310	630x437x16
SSC3026D	620x430x200	580x395x195	630x437x16
SSC3026E	620x425x250	580x395x245	630x437x16
SSC3026B	580x368x200	535x345x195	590x375x15
SSC3026C	580x368x165	535x345x155	590x375x15
SSC3016	420x310x155	380x280x145	413x310x10